

Laser Blade

iGuzzini

iGuzzini

Last information update: April 2025

Product configuration: MU77
MU77: Adjustable 15 - cell Recessed frame - LED - Warm white - DALI dimmable power supply - Spot Beam

MU77: Adjustable 15 - cell Recessed frame - LED - Warm white - DALI dimmable power supply - Spot Beam

MU77: Adjustable 15 - cell Recessed frame - LED - Warm white - DALI dimmable power supply - Spot Beam

Recessed rectangular luminaire with LEDs. Shaped steel sheet structural compartment with outer rim. The 15 lighting cells linear body, in die-cast aluminium, can be used to direct the emission with a tilting adjustability of $\pm 30^\circ$. Metallised thermoplastic high definition optics, integrated in a rear position in the black anti-glare screen; the structure of the optical system prevents a pinpoint effect, allowing precise, circular light distribution and emission with controlled luminance. Supplied with DALI dimmable control gear connected to the luminaire. Warm white LED.

recessed with mechanical blocking system for false ceilings from 1 to 25 mm; can be installed on ceilings and walls (vertical + horizontal) - preparation slot 80 x 428

Black / Black (43) | Black / White (47) | Grey / Black (74)*

* Colours on request

2.06

wall recessed|ceiling recessed

on power box: screw connections

dimming function with pushbutton (TOUCH DIM/PUSH): for this option consult the instructions included in the package

Complies with EN60598-1 and pertinent regulations



Im system:	2624	CRI (typical):	92
W system:	33.5	Colour temperature [K]:	3000
Im source:	3200	MacAdam Step:	3
W source:	30	Life Time LED 1:	> 50,000h - L90 - B10 (Ta 25°C)
Luminous efficiency (Im/W, real value):	78.3	Lamp code:	LED
Im in emergency mode:	-	Number of lamps for optical assembly:	1
Total light flux at or above an angle of 90° [Lm]:	0	ZVEI Code:	LED
Light Output Ratio (L.O.R.) [%]:	82	Number of optical assemblies:	1
Beam angle [°]:	14°	Control:	DALI-2
CRI (minimum):	90		

Imax=25144 cd	Lux			
	h	d	Em	Emax
	2	0.5	4875	6286
	4	1	1219	1571
	6	1.5	542	698
$\alpha = 14^\circ$	8	2	305	393

Utilisation factors

R	77	75	73	71	55	53	33	00	DRR
K0.8	74	70	68	66	70	67	67	64	78
1.0	77	74	72	70	73	71	71	68	83
1.5	81	79	77	75	78	76	75	73	89
2.0	84	82	80	79	81	79	78	76	93
2.5	85	84	83	82	83	82	81	79	96
3.0	86	85	84	84	84	83	82	80	98
4.0	87	86	86	85	85	85	83	82	99
5.0	88	87	87	87	86	85	84	82	100
