

## Blade R downlight


Design iGuzzini

iGuzzini

Last information update: April 2025

### Product configuration: PB21.01

PB21: accessory cover with swivel module - Spot beam



### Product code

PB21: accessory cover with swivel module - Spot beam

### Technical description

Round swivel luminaire with 355° internal rotation and max 30 tipping movement, designed to use LED lamps with C.o.B. technology. Version compatible with Blade R diam 170mm (18LED) complete with device for coupling it to the luminaire and DALI control gear. The main swivel body is made of die-cast aluminium with a radiant surface that guarantees optimum heat dissipation. Metallised, thermoplastic, high definition reflector - spot optic (16°). Structure with die-cast aluminium external surface frame. The internal ring is made of thermoplastic available in a range of painted and metallised finishes. Safety glass included Product complete with LED with a 3000K colour tone and high colour rendering index CRI90.

### Installation


Downlight accessory for Blade R diam 170mm (18LED)

### Colour

White (01)

### Weight (Kg)

0.37



Complies with EN60598-1 and pertinent regulations



IP20

IP23

On the visible part of the product once installed



### Technical data

Im system:	956.3	CRI:	90
W system:	12.0	Colour temperature [K]:	3000
Im source:	1310	MacAdam Step:	2
W source:	10	Life Time LED 1:	> 50,000h - L90 - B10 (Ta 25C)
Luminous efficiency (Im/W, real value):	79.69	Lamp code:	LED
Im in emergency mode:	-	Number of lamps for optical assembly:	1
Total light flux at or above an angle of 90° [Lm]:	0.0	ZVEI Code:	LED
Light Output Ratio (L.O.R.) [%]:	73	Number of optical assemblies:	1
Beam angle [°]:	20°	Control:	DALI-2