


Last information update: November 2024

**Product configuration: QA88+QB21.01**

QA88: Module for continuous lineFrame DownGeneral LightL 898

QB21.01: Down LO plate - DALI - General Light - LED Warm - L 896 - 12.5W 1375lm - 3000K - White

**Product code**

QA88: Module for continuous lineFrame DownGeneral LightL 898

**Technical description**

Extruded aluminium intermediate profile - Frame version with contact frame; this allows continuous lines to be created with other intermediate profiles and an initial profile (required). Methacrylate opal screen for diffused general light; screen set up for connecting several lengths by overlapping.

**Installation**

This can be recessed using the brackets on the profile; the mechanical systems for connecting the subsequent profiles are included in the package.

**Colour**

White (01)

**Weight (Kg)**

1.86

**Mounting**

ceiling recessed|ceiling pendant

**Wiring**

Set up to house the LED modules required by the system.

**Notes**

Take care with the system configuration. To make continuous lines of lighting, use the intermediate modules. To complete a continuous line correctly there must always be an initial module at the start or end of the composition.  
TPb rated. TPa version available on request, contact iGuzzini for more info

Complies with EN60598-1 and pertinent regulations

**Product code**

QB21.01: Down LO plate - DALI - General Light - LED Warm - L 896 - 12.5W 1375lm - 3000K - White

**Technical description**

LED module set up for housing in initial or intermediate system profiles. Down emission - Low Output version for General Light profiles (with opal diffuser screen). DALI dimmable control gear integrated in the luminaire. Extruded aluminium heat sink; high emission yield flux enhancer. Warm 3000K LED

**Installation**

Module insertion on profiles facilitated by a quick coupling system.

**Colour**

Indeterminate (00)

**Weight (Kg)**

0.99

**Wiring**

Quick coupling terminal block connection to simplify connections between the subsequent modules. Complete with integrated dimmable digital DALI control gear.

Complies with EN60598-1 and pertinent regulations

**Technical data**

Im system:	1444	CRI (minimum):	80
W system:	12.9	Colour temperature [K]:	3000
Im source:	1900	MacAdam Step:	3
W source:	11	Life Time LED 1:	> 50,000h - L90 - B10 (Ta 25°C)
Luminous efficiency (Im/W, real value):	111.9	Lamp code:	LED
Im in emergency mode:	-	Number of lamps for optical assembly:	1
Total light flux at or above an angle of 90° [Lm]:	0	ZVEI Code:	LED
Light Output Ratio (L.O.R.) [%]:	76	Number of optical assemblies:	1

Polar

