


Last information update: November 2024

**Product configuration: QA89+QB43.01**

QA89: Module for continuous lineFrame DownGeneral LightL 3596

QB43.01: Down HO plate - ON-OFF - General Light - LED Neutral - L 3588 - 72.5W 9045lm - 4000K - White

**Product code**

QA89: Module for continuous lineFrame DownGeneral LightL 3596

**Technical description**

Extruded aluminium intermediate profile - Frame version with contact frame; this allows continuous lines to be created with other intermediate profiles and an initial profile (required). Methacrylate opal screen for diffused general light; screen set up for connecting several lengths by overlapping.

**Installation**

This can be recessed using the brackets on the profile; the mechanical systems for connecting the subsequent profiles are included in the package.

**Colour**

White (01)

**Weight (Kg)**

7.4

**Mounting**

ceiling recessed|ceiling pendant

**Wiring**

Set up exclusively to house L 3588 triple-length LED modules.

**Notes**

Take care with the system configuration. To make continuous lines of lighting, use the intermediate modules. To complete a continuous line correctly there must always be an initial module at the start or end of the composition.  
TPb rated. TPa version available on request, contact iGuzzini for more info

Complies with EN60598-1 and pertinent regulations

**Product code**

QB43.01: Down HO plate - ON-OFF - General Light - LED Neutral - L 3588 - 72.5W 9045lm - 4000K - White **Attention! Code no longer in production**

**Technical description**

LED module set up for housing in intermediate system profiles, ideal for particularly long light lines. Down emission - High Output version for General Light profiles (with opal diffuser screen). The module optic and structural fittings allow high luminous flux and system efficiency values. Electronic control gear integrated in the luminaire. Extruded aluminium heat sink; high emission yield flux enhancer. Neutral 4000K LED

**Installation**

Module insertion on profiles facilitated by a quick coupling system.

**Colour**

Indeterminate (00)

**Weight (Kg)**

3.8

**Wiring**

Quick coupling terminal block connection to simplify connections between the subsequent modules. Complete with integrated ON-OFF - non-dimmable control gear.

**Notes**

Important: the triple length intermediate luminous module can be used for both initial profiles - L 3594 - for stand-alone applications, and intermediate profiles - L 3594 - for continuous line applications.

Complies with EN60598-1 and pertinent regulations

**Technical data**

lm system:	9424	CRI (minimum):	80
W system:	74.9	Colour temperature [K]:	4000
lm source:	12400	MacAdam Step:	3
W source:	67	Life Time LED 1:	> 50,000h - L90 - B10 (Ta 25°C)
Luminous efficiency (lm/W, real value):	125.8	Lamp code:	LED
lm in emergency mode:	-	Number of lamps for optical assembly:	1
Total light flux at or above an angle of 90° [Lm]:	0	ZVEI Code:	LED
Light Output Ratio (L.O.R.) [%]:	76	Number of optical assemblies:	1

Polar

