

Last information update: November 2024

**Product configuration: QB13+QZ61.01**

QB13: Down LO plate - DALI - General Light - LED Neutral - L 896

QZ61.01: Module for continuous line - Minimal Down - General Light - L 898 - TP(a) - White

**Product code**

QB13: Down LO plate - DALI - General Light - LED Neutral - L 896

**Technical description**

LED module set up for housing in initial or intermediate system profiles. Down emission - Low Output version for General Light profiles (with opal diffuser screen). DALI dimmable control gear integrated in the luminaire. Extruded aluminium heat sink; high emission yield flux enhancer. Neutral 4000K LED

**Installation**

Module insertion on profiles facilitated by a quick coupling system.

**Colour**

Indeterminate (00)

**Weight (Kg)**

0.99

**Wiring**

Quick coupling terminal block connection to simplify connections between the subsequent modules. Complete with integrated dimmable digital DALI control gear.

Complies with EN60598-1 and pertinent regulations

**Product code**

QZ61.01: Module for continuous line - Minimal Down - General Light - L 898 - TP(a) - White

**Technical description**

Extruded aluminium intermediate profile - Minimal (frameless) version for flush with ceiling mounting; this allows continuous lines to be created with other intermediate profiles and an initial profile (required). Polycarbonate screen for diffused general light in compliance with the TP(a) standard; screen set up for connecting different lengths by overlapping.

**Installation**

Installation can be recessed, surface, ceiling and pendant-mounted using suitable accessories to be ordered separately; the mechanical systems for connecting the subsequent profiles are included in the package.

**Colour**

White (01)

**Weight (Kg)**

1.66

**Mounting**

ceiling recessed|ceiling surface|ceiling pendant

**Wiring**

Set up to house the LED modules required by the system.

**Notes**

Take care with the system configuration. To make continuous lines of lighting, use the intermediate modules. To complete a continuous line correctly there must always be an initial module at the start or end of the composition.

Complies with EN60598-1 and pertinent regulations

**Technical data**

lm system:	1292	CRI (minimum):	80
W system:	11	Colour temperature [K]:	4000
lm source:	2050	MacAdam Step:	3
W source:	11	Lamp code:	LED
Luminous efficiency (lm/W, real value):	117.4	Number of lamps for optical assembly:	1
lm in emergency mode:	-	ZVEI Code:	LED
Total light flux at or above an angle of 90° [Lm]:	0	Number of optical assemblies:	1
Light Output Ratio (L.O.R.) [%]:	63	Control:	DALI-2

Polar

