

Product configuration: QB22+QA92.01

QB22: Down LO plate - DALI - General Light - LED Warm - L 1196
QA92.01: Initial module - Minimal Down - General Light - L 2397 - White

QB22: Down LO plate - DALI - General Light - LED Warm - L 1196

LED module set up for housing in initial or intermediate system profiles. Down emission - Low Output version for General Light profiles (with opal diffuser screen). DALI dimmable control gear integrated in the luminaire. Extruded aluminium heat sink; high emission yield flux enhancer. Warm 3000K LED

Module insertion on profiles facilitated by a quick coupling system.

Colour	Weight (Kg)
Indeterminate (00)	1.28

Quick coupling terminal block connection to simplify connections between the subsequent modules. Complete with integrated dimmable digital DALI control gear.

Complies with EN60598-1 and pertinent regulations



QA92.01: Initial module - Minimal Down - General Light - L 2397 - White

Initial profile in extruded aluminium - Minimal (frameless) version for flush with ceiling mounting and up-down emission; methacrylate opal screen for diffused general light; screen set up for connecting several lengths by overlapping.

Installation can be recessed, surface, ceiling and pendant-mounted using suitable accessories to be ordered separately. The initial modules can be used individually for various applications if completed with accessory caps and the required LED module.


Colour	Weight (Kg)
White (01)	4.7

ceiling recessed|ceiling surface|ceiling pendant

Setting up the LED modules
Set up to house the LED modules required by the system.

Take care with the system configuration. To make continuous lines of lighting, use the intermediate modules. To complete a continuous line correctly there must always be an initial module at the start or end of the composition.

Complies with EN60598-1 and pertinent regulations



Im system:	3838	CRI (minimum):	80
W system:	30	Colour temperature [K]:	3000
Im source:	5050	MacAdam Step:	3
W source:	30	Lamp code:	LED
Luminous efficiency (lm/W, real value):	127.9	Number of lamps for optical assembly:	1
Im in emergency mode:	-	ZVEI Code:	LED
Total light flux at or above an angle of 90° [Lm]:	0	Number of optical assemblies:	1
Light Output Ratio (L.O.R.) [%]:	76	Control:	DALI-2

Polar

