

Last information update: November 2024

#### Product configuration: QB22+QZ58.01

QB22: Down LO plate - DALI - General Light - LED Warm - L 1196

QZ58.01: Initial module - Minimal Down - General Light - L 1208 - TP(a) - White

#### Product code

QB22: Down LO plate - DALI - General Light - LED Warm - L 1196

#### Technical description

LED module set up for housing in initial or intermediate system profiles. Down emission - Low Output version for General Light profiles (with opal diffuser screen). DALI dimmable control gear integrated in the luminaire. Extruded aluminium heat sink; high emission yield flux enhancer. Warm 3000K LED

#### Installation

Module insertion on profiles facilitated by a quick coupling system.

#### Colour

Indeterminate (00)

#### Weight (Kg)

1.28

#### Wiring

Quick coupling terminal block connection to simplify connections between the subsequent modules. Complete with integrated dimmable digital DALI control gear.

Complies with EN60598-1 and pertinent regulations



#### Product code

QZ58.01: Initial module - Minimal Down - General Light - L 1208 - TP(a) - White

#### Technical description

Initial profile in extruded aluminium - Minimal (frameless) version for flush with ceiling installation; polycarbonate screen for diffused general light in compliance with the TP(a) standard; screen set up for connecting several lengths by overlapping.

#### Installation

Installation can be recessed, surface, ceiling and pendant-mounted using suitable accessories to be ordered separately. The initial modules can be used individually for various applications if completed with accessory caps and the required LED module.

#### Colour

White (01)

#### Weight (Kg)

2.35

#### Mounting

ceiling recessed|ceiling surface|ceiling pendant


#### Wiring

Set up to house the LED modules required by the system.

#### Notes

Take care with the system configuration. To make continuous lines of lighting, use the intermediate modules. To complete a continuous line correctly there must always be an initial module at the start or end of the composition.

Complies with EN60598-1 and pertinent regulations



#### Technical data

Im system:	1607	CRI (minimum):	80
W system:	15	Colour temperature [K]:	3000
Im source:	2550	MacAdam Step:	3
W source:	15	Lamp code:	LED
Luminous efficiency (Im/W, real value):	107.1	Number of lamps for optical assembly:	1
Im in emergency mode:	-	ZVEI Code:	LED
Total light flux at or above an angle of 90° [Lm]:	0	Number of optical assemblies:	1
Light Output Ratio (L.O.R.) [%]:	63	Control:	DALI-2

Polar

