

Last information update: November 2024

Product configuration: QB31+QA98.01

QB31: Up / Down LO plate - DALI - General Light - LED Warm - L 3588

QA98.01: Initial module - Minimal Up / Down - General Light - L 3596 - White

Product code

QB31: Up / Down LO plate - DALI - General Light - LED Warm - L 3588

Technical description

LED module set up for housing in intermediate system profiles, ideal for particularly long light lines. Up + down emission - Low Output version for General Light profiles (with lower opal diffuser screen). DALI dimmable control gear integrated in the luminaire. Extruded aluminium heat sink; high emission yield flux enhancer. Warm 3000K LED

Installation

Module insertion on profiles facilitated by a quick coupling system.

Colour

Indeterminate (00)

Weight (Kg)

4.8

Wiring

Quick coupling terminal block connection to simplify connections between the subsequent modules. Complete with integrated dimmable DALI control gear.

Notes

Important: the triple length intermediate luminous module can be used for both initial profiles - L 3594 - for stand-alone applications, and intermediate profiles - L 3594 - for continuous line applications.

Complies with EN60598-1 and pertinent regulations



Product code

QA98.01: Initial module - Minimal Up / Down - General Light - L 3596 - White

Technical description

Initial profile in extruded aluminium - Minimal (frameless) version for flush with ceiling mounting available for direct and indirect lighting (luminous flux split into approx. 70% down / 30% up.); methacrylate opal lower screen for diffused general light; screen set up for connecting several lengths by overlapping. Methacrylate diffusing screen for upper emission.

Installation

Installation can be pendant-mounted using suitable accessories to be ordered separately. The initial modules can be used individually for various applications if completed with accessory caps and the required LED module - L 3588.

Colour

White (01)

Weight (Kg)

7

Mounting

ceiling pendant

Wiring

Set up exclusively to house L 3588 triple-length LED modules.

Notes



Take care with the system configuration. To make continuous lines of lighting, use the intermediate modules. To complete a continuous line correctly there must always be an initial module at the start or end of the composition.

Complies with EN60598-1 and pertinent regulations



Technical data

lm system:	8015	CRI (minimum):	80
W system:	68	Colour temperature [K]:	3000
lm source:	11450	MacAdam Step:	3
W source:	68	Lamp code:	LED
Luminous efficiency (lm/W, real value):	117.9	Number of lamps for optical assembly:	1
lm in emergency mode:	-	ZVEI Code:	LED
Total light flux at or above an angle of 90° [Lm]:	2266	Number of optical assemblies:	1
Light Output Ratio (L.O.R.) [%]:	70	Control:	DALI-2



Polar

