

Palco Low Voltage


Design Artec
Studio

iGuzzini

Last information update: June 2025

Product configuration: PU85

PU85: Palco LV spotlight Ø 62 - Spot beam



Product code

PU85: Palco LV spotlight Ø 62 - Spot beam

Technical description

Adjustable spotlight with adapter for installation on a 48V Filorail low voltage track. The thermoplastic adapters are designed so they can be installed even in the curved track sections. Die-cast aluminium body with an ideal passive dissipation system to guarantee a long life and effective heat management. Driver circuit with DALI Powerline technology that allows each spotlight on the track to be adjusted independently. This offers a remarkable level of flexibility and lighting control. The swivel joints allow the spotlight to be rotated by 360° and tilted by 90°. The set back position of the optic unit guarantees a high level of visual comfort. OptiBeam LENS lighting system with hi-tech optic lens that creates a particularly well-defined light beam. A rapid tool-free system for connecting the adapter electrically and mechanically to the track.

Installation

On a low voltage Filorail track. A tool-free system for connecting the product electrically and mechanically to the track.

Colour

White (01) | Black (04)

Weight (Kg)

0.35

Mounting

Low voltage track

Wiring

LED driver integrated in product body - direct connection on 48V track. Track power supply unit to be ordered separately.

Notes

Technical and anti-glare accessories available; with option of the combined installation of two internal accessories.

Complies with EN60598-1 and pertinent regulations

IP20

Technical data

Im system:	1332.1	MacAdam Step:	2
W system:	18.0	Life Time LED 1:	> 50,000h - L90 - B10 (Ta 25C)
Im source:	1730	Voltage [Vin]:	48
W source:	17	Lamp code:	LED
Luminous efficiency (Im/W, real value):	74.01	Number of lamps for optical assembly:	1
Im in emergency mode:	-	ZVEI Code:	LED
Total light flux at or above an angle of 90° [Lm]:	0.0	Number of optical assemblies:	1
Light Output Ratio (L.O.R.) [%]:	77	LED current [mA]:	0.45
Beam angle [°]:	15°	Power factor:	See installation instructions
CRI:	90	Overvoltage protection:	0kV Common mode & 0kV Differential mode
Colour temperature [K]:	4000	Control:	DALI