

**LIGHT UP WALK**

**#I.B032- -13**

VOLTAGE FINISH


In-ground recessed luminaire with a symmetrical optic. Cast aluminum body and outer casing. Trim and vandal resistant screws are made of stainless steel. The double layer of tempered glass reduces the surface temperature. The total assembly can withstand a load of 5000 Kg (11 000 lbs) at a maximum speed of 50 Km/h (31 mph).

**LAMPING:** 1 X 10 W XELOGEN, 12 V LOW VOLTAGE, G4 BASE


**PROJECT NAME:** \_\_\_\_\_

**TYPE:** \_\_\_\_\_


LAST UPDATE: FEBRUARY 24th, 2009



**TOP VIEW**



**ISOMETRIC VIEW**



**SECTION VIEW**

**ACCESSORIES  
TO BE ORDERED SEPERATELY**



☐ I-B900 - CASING



☐ I-B958 - CASING  
MULTIPLE FEEDER  
13-1/8" X 10-1/8" X 5-1/2" H.



☐ I-B916 - SUCTION CUP



☐ B917 - COLORED FILTERS

05 - RED  
06 - YELLOW  
09 - BLUE

**VOLTAGE** ☐ 120 V

**METAL FINISH** ☐ 13 - STAINLESS STEEL



5455 de Gaspé  
suite 100, Montréal (Québec)  
Canada H2T 3B3  
P.: 514.523.1339 F.: 514.525.6107

**LIGHT UP WALK  
PROFESSIONEL**