

LIGHT UP WALK

PROFESSIONEL

#I.B002- - **13**
VOLTAGE FINISH


In-ground recessed luminaire with wall an adjustable optic of +/- 12°. Cast aluminum body and outer casing. Trim and vandal resistant screws are made of stainless steel. The double layer of tempered glass reduces the surface temperature. The total assembly can withstand a load of 5000 Kg (11 000 lbs) at a maximum speed of 50 Km/h (31 mph).

LAMPING: 1 X 20 W MR-11 HALOGEN, 12 V LOW VOLTAGE, GU4 BASE.


PROJECT NAME: _____

TYPE: _____

LAST UPDATE: FEBRUARY 24th, 2009




TOP VIEW



ISOMETRIC VIEW

USE REMOTE TRANSFORMER (NOT INCLUDED)



SECTION VIEW

ACCESSORIES TO BE ORDERED SEPARATELY



○ I-B900 - CASING



○ I.B958 - CASING
MULTIPLE FEEDER
13-1/8" X 10-1/8" X 5-1/2" H.



○ I-B916 - SUCTION CUP



○ B917 - COLORED FILTERS

05 - RED
06 - YELLOW
09 - BLUE

VOLTAGE ○ 120 V

METAL FINISH ○ 13 - STAINLESS STEEL



5455 de Gaspé
suite 100, Montréal (Québec)
Canada H2T 3B3
P.: 514.523.1339 F.: 514.525.6107

**LIGHT UP WALK
PROFESSIONEL**