


Last information update: February 2025

Product configuration: R608

R608: Minimal section 3 x 5 LEDs - Wall Washer



Product code

R608: Minimal section 3 x 5 LEDs - Wall Washer

Technical description

Linear recessed miniaturised luminaire for LED lamps, specialised for vertical wall lighting. The patented optic system guarantees a homogeneous and effective emission on the wall, as well as avoiding shadow zones near the ceiling. Main body with die-cast aluminium radiant surface, minimal (frameless) version for mounting flush with the ceiling. For recessed installation in a false ceiling a specific adapter is required that is available with a separate item code. Flux enhancer - superpure aluminium reflector - asymmetrical textured PMMA screen - black polycarbonate internal perimeter frame. Supplied with a power supply unit connected to the luminaire.

Installation

The recess body is inserted in the specific adapter installed previously by means of a steel wire spring - check the thickness of the false ceiling and use a compatible frame available with a separate item code.

Colour

Black (04)

Weight (Kg)


0.86

Mounting

wall recessed|ceiling recessed

Wiring

on power supply box: screw connections.




Complies with EN60598-1 and pertinent regulations



Technical data

lm system:	1400	CRI (typical):	92
W system:	33.6	Colour temperature [K]:	4000
lm source:	3500	MacAdam Step:	3
W source:	29	Life Time LED 1:	> 50,000h - L90 - B10 (Ta 25°C)
Luminous efficiency (lm/W, real value):	41.7	Lamp code:	LED
lm in emergency mode:	-	Number of lamps for optical assembly:	1
Total light flux at or above an angle of 90° [Lm]:	0	ZVEI Code:	LED
Light Output Ratio (L.O.R.) [%]:	40	Number of optical assemblies:	1
CRI (minimum):	90	Control:	DALI-2

Polar



Illuminances

Lux		Wall distance = 1m																			
3																					
	3	8	18	48	144	259	144	48	18	8	3										
2	6	12	25	60	138	194	138	60	25	12	6										
	7	13	26	60	111	141	111	60	26	13	7										
1	7	12	25	49	77	92	77	49	25	12	7										
	6	12	22	36	50	57	50	36	22	12	6										
0																					
	m	-2	-1	0	1	2	3														