Design iGuzzini

iGuzzini

Last information update: July 2025

Product configuration: PT38.01+RU50.38

PT38.01: Surface/pendant-mounted corner module - Down - GL HO - DALI - - 24.5W 3285.6lm - 3500K - White

RU50.38: Single Opal screen L=1200 (GL) - Opaline



Product code

PT38.01: Surface/pendant-mounted corner module - Down - GL HO - DALI - - 24.5W 3285.6lm - 3500K - White

Technical description

Minimal surface/pendant-mounted corner element; including a 3500K LED module, General Light High Output (HO) version. Integrated DALI dimmable power supply with pass-through wiring for continuous lines. The module optic and structural fittings allow high luminous flux and system efficiency values. Product complete with a "Furukawa" reflective screen that further increases its efficiency. Extruded aluminium heat sink and "Halogen Free" electric cables. Element with light not including a screen but compatible with both roll and single Opal screens.

Installation

Recessed

 Colour
 Weight (Kg)

 White (01)
 3.02



639

Wiring

Quick coupling terminal block connection to simplify connections between the subsequent modules. Complete with integrated dimmable DALI power supply.

Complies with EN60598-1 and pertinent regulations













Accessory code

RU50.38: Single Opal screen L=1200 (GL) - Opaline

Technical description

Flexible single Opal screen for composition L=1200 - General Light optic -

Installation

snapped on via special springs located in the profile

Colour

Opaline (38)

Notes

TPa version available on request, contact iGuzzini for more info.

Complies with EN60598-1 and pertinent regulations

Technical	data
I CCIIIIICai	uata

Rf (Colour Fidelity Index):

	lm system:	3286	Rg (Gamut Index):	94
	W system:	24.5	Colour temperature [K]:	3500
	lm source:	2220	MacAdam Step:	3
	W source:	11	Life Time LED 1:	> 50,000h - L90 - B10 (Ta 25°C)
	Luminous efficiency (lm/W, 134.1 real value):	Lamp code:	LED	
			Number of lamps for optical	1
	Im in emergency mode:	-	assembly:	
	Total light flux at or above	0	ZVEI Code:	LED
	an angle of 90° [Lm]:		Number of optical	2
	Light Output Ratio (L.O.R.) 7- [%]:	74	assemblies:	
			Control:	DALI-2
1	CRI (minimum):	80		

Polar

