


Last information update: June 2024

Product configuration: UI49+X197.04

UI49: Floor recessed Earth D=144mm - Neutral White - Wide Flood Optic - DALI

X197.04: Plastic casing for installation on floors + end cap - Black

**Product code**

UI49: Floor recessed Earth D=144mm - Neutral White - Wide Flood Optic - DALI

Technical description

Recessed luminaire that can be installed in floors or in the ground. It is designed to use white monochrome LED lamps, for lighting, fixed optic with built-in dimming DALI electronic control gear. The D = 144 mm round frame has an AISI 304 stainless steel body and frame and an extra-clear, sodium - calcium tempered glass cover, with a thickness of 12 mm. The stainless steel body is painted black. The luminaire is fixed to the outer casing with two Torx screws that hold it in place. It includes the LED circuit, aluminium OPTI BEAM reflector and black plastic casing cover. The electronic ballast is integrated in the product. The product's wiring system features an A2 stainless steel cable gland with a 1200mm long A075RNF type 4x1 mm² output power cable. The cable is equipped with an anti-transpiration device (IP68) that consists of a silicone-coated joint located on the power cable. An outer casing is available for installation and it can be ordered separately from the plastic optic assembly. The glass unit, optic assembly, frame and outer casing together guarantee a maximum static load resistance of 5000 kg. The maximum surface temperature of the glass is less than 40°C.

Installation

The product is secured to the outer casing with two Torx screws. The luminaire can be installed recessed with outer case in the floor or in the ground.

Colour

Steel (13)

Weight (Kg)

1.91

Mounting

Floor recessed|ground recessed

Wiring

Product includes dimming DALI control gear 220÷240Vac.

Notes

IP68 degree of protection on the product and cable when using IP68 connectors * The product is not suitable for installation in swimming pools and fountains. Overvoltage protection: 4KV Common mode, 3,5KV differenzial mode


Complies with EN60598-1 and pertinent regulations



Complete immersion for limited periods, not suitable for use in swimming pools or fountains.



The lighting fixtures were designed and tested to withstand a static load of up to 50000 N and to resist drive-over stress by vehicles with tires. The fixtures cannot be used in lanes subjected to horizontal stresses due to acceleration, braking and / or changes of direction.

**Accessory code**

X197.04: Plastic casing for installation on floors + end cap - Black

Technical description

Made of plastic (polypropylene). Inclusive of front cap with system for extracting the cables and double cable entry.

Installation

Floor-standing (concrete)

Colour

Black (04)


Weight (Kg)

0.88

Mounting

ground surface|Floor recessed|ground recessed

Complies with EN60598-1 and pertinent regulations



Technical data

| | | | |
|--|--------------------------------|--|--|
| Im system: | 1342 | Life Time LED 2: | 100,000h - L90 - B10 (Ta 40°C) |
| W system: | 11.7 | Lamp code: | LED |
| Im source: | 1700 | Number of lamps for optical assembly: | 1 |
| W source: | 9.8 | ZVEI Code: | LED |
| Luminous efficiency (Im/W, real value): | 114.7 | Number of optical assemblies: | 1 |
| Im in emergency mode: | - | Intervallo temperatura ambiente: | from -25°C to 50°C. |
| Total light flux at or above an angle of 90° [Lm]: | 1342 | Power factor: | See installation instructions |
| Light Output Ratio (L.O.R.) [%]: | 79 | Inrush current: | 5 A / 50 µs |
| Beam angle [°]: | 56° | Maximum number of luminaires of this type per miniature circuit breaker: | B10A: 31 luminaires B16A: 50 luminaires C10A: 52 luminaires C16A: 85 luminaires |
| CRI (minimum): | 80 | Minimum dimming %: | 1 |
| Colour temperature [K]: | 4000 | Overvoltage protection: | /kV Common mode & /kV Differential mode |
| MacAdam Step: | 2 | Control: | DALI-2 |
| Life Time LED 1: | 100,000h - L90 - B10 (Ta 25°C) | | |

Polar

