

## Laser Blade XS



Design iGuzzini

iGuzzini

Last information update: June 2025

### Product configuration: Q879

Q879: Ceiling-mounted LB XS Linear HC - 5 cells - Flood beam - remote driver



### Product code

Q879: Ceiling-mounted LB XS Linear HC - 5 cells - Flood beam - remote driver

### Technical description

Ceiling-mounted luminaire with 5 optic elements for LED lamps - fixed optics with metallised thermoplastic high definition Opti-Beam reflectors. Despite the ultracompact size of the product, the patented technology of the optic system guarantees an efficient luminous flux and a high level of controlled glare visual comfort. Extruded aluminium main body and technical dissipation unit - shaped steel fixing plate. Ballast not included, available with separate code.

### Installation

Ceiling-mounted with surface fixing plate (screws and screw anchors not included) - external locking system.

### Colour

White (01) | Black / Black (43) | Black / White (47) | White/Gold (41)\* | Black/gold (44)\* | White / burnished chrome (E7)\* | Black/burnished chrome (F1)\*

### Weight (Kg)

0.15

\* Colours on request

### Mounting

ceiling surface

### Wiring

Cables supplied with quick-coupling terminals for connecting to power supply line.

Complies with EN60598-1 and pertinent regulations




### Technical data

Im system:	780	CRI (minimum):	90
W system:	10	Colour temperature [K]:	3000
Im source:	940	MacAdam Step:	2
W source:	10	Life Time LED 1:	> 50,000h - L80 - B10 (Ta 25°C)
Luminous efficiency (Im/W, real value):	78	Lamp code:	LED
Im in emergency mode:	-	Number of lamps for optical assembly:	1
Total light flux at or above an angle of 90° [Lm]:	0	ZVEI Code:	LED
Light Output Ratio (L.O.R.) [%]:	83	Number of optical assemblies:	1
Beam angle [°]:	43°	LED current [mA]:	700

### Polar

Imax=1602 cd		Lux			
90°	180°	h	d	Em	E <sub>max</sub>
		2	1.5	326	398
		4	3.1	82	99
		6	4.6	36	44
		8	6.1	20	25
α=42°					

### Isolux



### UGR diagram

Corrected UGR values (at 940 lm bare lamp luminous flux)											
Reflect.:		viewed crosswise					viewed endwise				
ceiling		0.70	0.70	0.50	0.50	0.30	0.70	0.70	0.50	0.50	0.30
walls		0.50	0.30	0.50	0.30	0.30	0.50	0.30	0.50	0.30	0.30
work pl.		0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20
Room dim		viewed crosswise					viewed endwise				
x	y										
2H	2H	7.3	7.8	7.6	8.0	8.3	7.3	7.8	7.6	8.0	8.3
	3H	7.2	7.6	7.5	7.9	8.2	7.2	7.6	7.5	7.9	8.2
	4H	7.1	7.5	7.5	7.8	8.1	7.1	7.5	7.5	7.8	8.1
	6H	7.1	7.4	7.4	7.7	8.1	7.1	7.4	7.4	7.7	8.1
	8H	7.0	7.4	7.4	7.7	8.0	7.0	7.4	7.4	7.7	8.0
	12H	7.0	7.3	7.4	7.7	8.0	7.0	7.3	7.4	7.7	8.0
4H	2H	7.1	7.5	7.5	7.8	8.1	7.1	7.5	7.5	7.8	8.1
	3H	7.0	7.3	7.4	7.7	8.0	7.0	7.3	7.4	7.7	8.0
	4H	6.9	7.2	7.3	7.6	8.0	6.9	7.2	7.3	7.6	8.0
	6H	6.8	7.1	7.2	7.5	7.9	6.8	7.1	7.2	7.5	7.9
	8H	6.8	7.0	7.2	7.4	7.9	6.8	7.0	7.2	7.4	7.9
	12H	6.7	7.0	7.2	7.4	7.8	6.7	6.9	7.2	7.4	7.8
8H	4H	6.8	7.0	7.2	7.4	7.9	6.8	7.0	7.2	7.4	7.9
	6H	6.7	6.9	7.1	7.3	7.8	6.7	6.9	7.1	7.3	7.8
	8H	6.6	6.8	7.1	7.3	7.8	6.6	6.8	7.1	7.3	7.8
	12H	6.6	6.7	7.1	7.2	7.7	6.6	6.7	7.1	7.2	7.7
12H	4H	6.7	6.9	7.2	7.4	7.8	6.7	7.0	7.2	7.4	7.8
	6H	6.6	6.8	7.1	7.3	7.8	6.6	6.8	7.1	7.3	7.8
	8H	6.6	6.7	7.1	7.2	7.7	6.6	6.7	7.1	7.2	7.7
Variations with the observer position at spacing:											
S =		1.0H	7.0	/ -14.5				7.0	/ -14.5		
		1.5H	9.8	/ -14.7				9.8	/ -14.7		
		2.0H	11.8	/ -14.8				11.8	/ -14.8		