


Ultimo aggiornamento delle informazioni: Dicembre 2024

**Configurazione di prodotto: BT08**

BT08: Linealuce Mini - Wall-/Ceiling-mounted - Neutral White LED - 48V dc DMX512-RDM dimmable - L=1496mm - Wall Grazing Optic

**Codice prodotto**

BT08: Linealuce Mini - Wall-/Ceiling-mounted - Neutral White LED - 48V dc DMX512-RDM dimmable - L=1496mm - Wall Grazing Optic

**Descrizione tecnica**

Direct light luminaire, designed to use monochrome LED lamps, 48V dc DMX512-RDM dimmable. Ceiling- and wall-mounted. Consists of a body, a box for DMX driver and supports for installation (to be ordered separately). Extruded aluminium body and side box, with zamak die-cast end caps complete with silicone seals. Coated with liquid acrylic paint with a high level of weather and UV ray resistance. The top of the optical assembly is closed by a 3 mm thick transparent glass screen, fixed with silicone. Complete with multi-LED plate in Neutral White, side box with 48V dc DMX512-RDM electronic driver (ballast to be ordered separately). Side box with double PG13.5 cable gland and outlet cables for pass-through wiring. Fitted with a PMMA diffusing filter and optics with plastic (methacrylate) lens for Wall Grazing lighting. All external screws used are made of A2 stainless steel. The luminaire technical characteristics conform to EN 60598-1 standards and particular requirements.

**Installazione**

The following accessories are available for installation: adjustable wall-mounted arms in AISI304 stainless steel (L=200mm code BZJ8) and a plate for surface- or ceiling-mounting made of anodised aluminium (BZJ7).

**Colore**

Grigio (15)

**Peso (Kg)**

2.87

**Montaggio**

a parete/a soffitto

**Cablaggio**

The product is equipped with a nickel-plated brass PG13.5 double cable gland with H07RN-F rubber outlet cables 5x1.5mm<sup>2</sup> for pass-through wiring: each cable is set up both for the DMX-RDM signal and for 48V dc power supply. Available for electrical connection: IP68 5-pin linear connector (BZS6), cap for IP68 connectors + 120 Ohm terminating resistor (BZQ7), 48V dc DIN bar electronic ballasts to be ordered separately: 120W (BZ14), 240W (BZ15) and 480W (BZ16). DMX specifications require the insertion of a 120 Ohm terminating resistor to be placed between the DATA+ and DATA- cables of the last product in the line (code BZQ7)

**Note**


Product complete with LED lamp. DMX specifications require the insertion of a 120 Ohm terminating resistor to be placed between the DATA+ and DATA- cables of the last product in the line (code BZQ7)

Soddisfa EN60598-1 e relative note

**Dati tecnici**

|  |      |  |                                  |
|--|------|--|----------------------------------|
| Im di sistema:                               | 2048 | Life Time LED 1:                           | 100,000h - L80 - B10 (Ta 25°C)   |
| W di sistema:                                | 43.2 | Life Time LED 2:                           | 66,000h - L80 - B10 (Ta 40°C)    |
| Im di sorgente:                              | 3730 | Voltaggio [Vin]:                           | 48                               |
| W di sorgente:                               | 38   | Codice lampada:                            | LED                              |
| Efficienza luminosa (lm/W, dati di sistema): | 47.4 | Numero di lampade per vano ottico:         | 1                                |
| Im in modalità emergenza:                    | -    | Codice ZVEI:                               | LED                              |
| Flusso totale emesso a 90° o superiore [Lm]: | 0    | Numero di vani ottici:                     | 1                                |
| Light Output Ratio (L.O.R.) [%]:             | 55   | Intervallo temperatura ambiente operativa: | da -30°C a 50°C.                 |
| CRI (minimo):                                | 80   | Corrente LED [mA]:                         | 350                              |
| Temperatura colore [K]:                      | 4000 | Power factor:                              | Vedi istruzioni di installazione |
| MacAdam Step:                                | 3    | Control:                                   | DMX-RDM                          |

Polare



Illuminamenti

| Lux |   | Wall distance = 1m |     |    |    |    |    |    |    |    |     |     |
|-----|---|--------------------|-----|----|----|----|----|----|----|----|-----|-----|
| 3   |   | 0.4                | 0.8 | 2  | 4  | 10 | 14 | 10 | 5  | 2  | 1.0 | 0.5 |
| 2   |   | 2                  | 4   | 7  | 14 | 23 | 30 | 25 | 15 | 9  | 4   | 2   |
| 1   |   | 3                  | 6   | 10 | 19 | 31 | 40 | 34 | 21 | 12 | 6   | 4   |
| 0   |   | 4                  | 7   | 12 | 19 | 28 | 35 | 28 | 20 | 13 | 8   | 5   |
|     | m | -2                 | -1  | 0  | 1  | 2  | 3  |    |    |    |     |     |