Mini Reglette

**Design iGuzzini**   **iGuzzini**

Last information update: September 2020

Product configuration: 5278+L039
5278: Mini Reglette T16

Product code
5278: Mini Reglette T16 **Attention! Code no longer in production**

Technical description
High output luminaire for general lighting designed to use T16 fluorescent lamps. Extruded aluminium component-holding box. Polycarbonate standard protective screen. Joints for direct electric and mechanical connection included with the product. Simplified installation and maintenance. Ceiling/wall mounting kit included with the product. T16 fluorescent lamp included with colour temperature 3000°K.

Installation
Ceiling- and wall-mounted.

Colour
White (01)

Mounting
wall surface|ceiling surface

Wiring
The luminaire has a DALI electronic ballast

Complies with EN60598-1 and pertinent regulations

960°C   IP20   CE   EAC   A+

Technical data

lm system:	919,8	Colour temperature [K]:	3000
W system:	16	Ballast losses [W]:	2
lm source:	1200	Voltage [Vin]:	230
W source:	14	Lamp code:	L039
Luminous efficiency (lm/W, real value):	57,5	Socket:	G5
lm in emergency mode:	-	Number of lamps for optical assembly:	1
Total light flux at or above an angle of 90° [Lm]:	282,1	ZVEI Code:	T 16
Light Output Ratio (L.O.R.) [%]:	77	Number of optical assemblies:	1
CRI:	86	Control:	DALI

Polar

Imax=128 cd/Klm C175-355 γ=60° Lux/Klm

14 W
T 16 - G5

h	d1	d2	Em	Emax
1	-	2.5	43	102
2	-	4.9	11	26
3	-	7.4	5	11
4	-	9.9	3	6

Isolux

Lux
h=5 m.
$\alpha=0°$

T 16
G5
14 W

5   4   3.5   2.7   2.1   1.6   1.2   0.9   0.7

-1   0   1   2   3   4   5   6   7   8   9   m