

Last information update: November 2024

**Product configuration: S562**

S562: 47 surface Integral with side box - RGB - DMX - L = 610mm - Wall Grazing Wide Flood optic

**Product code**

S562: 47 surface Integral with side box - RGB - DMX - L = 610mm - Wall Grazing Wide Flood optic

**Technical description**

Direct light luminaire, designed to use RGB LED lamps, DMX512-RDM 220÷240Vac dimmable with searching and addressing function. Ceiling, wall or surface-mounted. It consists of a body and installation brackets to be ordered separately. The body is made of extruded aluminium and includes die-cast aluminium end caps with 50/60 Shore A silicone seals. It is subjected to a multi-step, pre-treatment process, in which the main phases are degreasing, fluorozirconation (a protective surface film) and sealing (with a nano-structured silane layer). The following painting stage consists of a primer and a liquid acrylic paint, cured at 150°C, with a high level of weather and UV ray resistance. The top of the optical assembly is closed by a 3 mm thick transparent glass screen, fixed with silicone. Complete with multi-LED plate in RGB colour and a 220÷240Vac DMX512-RDM electronic driver (power supply included). The product is supplied with a nickel-plated brass PG13.5 single cable gland with an H07RN-F 5x1, 5mm<sup>2</sup> rubber outlet cable with an IP68 male connector. Fitted with a PMMA diffusing filter and optics with a plastic (methacrylate) lens for Wide Flood lighting. All external screws used are made of A2 stainless steel.

**Installation**

Installation accessories can be purchased separately, including arms (for heights &lt; 3m and heights &gt; 3m) and plates.

**Colour**


White (01) | Black (04) | Grey (15) | Rust Brown (F5)

**Weight (Kg)**

2.48

**Mounting**

wall arm|wall surface



Complies with EN60598-1 and pertinent regulations

**Technical data**

lm system:	794	Life Time LED 2:	93,000h - L80 - B10 (Ta 40°C)
W system:	19.9	Voltage [Vin]:	230
lm source:	1260	Lamp code:	LED
W source:	14	Number of lamps for optical assembly:	1
Luminous efficiency (lm/W, real value):	39.9	ZVEI Code:	LED
lm in emergency mode:	-	Number of optical assemblies:	1
Total light flux at or above an angle of 90° [Lm]:	0	Intervallo temperatura ambiente:	from -30°C to 50°C.
Light Output Ratio (L.O.R.) [%]:	63	Control:	DMX-RDM
Life Time LED 1:	100,000h - L80 - B10 (Ta 25°C)		

**Polar**