

## Laser Blade


Design iGuzzini

iGuzzini

Last information update: May 2024

### Product configuration: N933

N933: High Contrast module L=1197 - direct emission with controlled glare - neutral white integrated DALI dimmable control gear



### Product code

N933: High Contrast module L=1197 - direct emission with controlled glare - neutral white integrated DALI dimmable control gear

**Attention! Code no longer in production**

### Technical description

direct emission modular lighting system. High Contrast module with 2 groups of 5 elements using fixed optic LED lamps - flood beam angle. The structure of the optical system produces light emission with controlled glare (UGR < 19). Minimal (frameless) version extruded aluminium profile; partial black methacrylate screens set up for connection to end caps on both sides. Installation can be surface-mounted (ceiling/wall), or pendant. The module must be completed with the accessories kit needed for the selected type of installation. DALI dimmable electronic control gear integrated in the luminaire. Neutral white high efficiency LED.

### Installation

pendant: complete with power supply unit with cable (MWG5) and suspension cables (MWG6); surface-mounted: complete with supports (MWG7).

### Colour

Aluminium (12)

### Weight (Kg)

2.02

### Mounting

ceiling recessed|ceiling surface|ceiling pendant

### Wiring

the module is fitted with 5-pin terminal blocks for pass-through wiring at the ends. DALI dimmable control gear integrated in the module.

### Notes

High Contrast modules may be completed with accessory end caps (code MX80) and used independently in the various applications. To make continuous lines, use accessory code MX81 with partial screen suitable for overlapping with other modules. Possibility of combined High Contrast / Low Contrast

Complies with EN60598-1 and pertinent regulations



### Technical data

Im system:	1742	CRI:	95
W system:	28	Colour temperature [K]:	4000
Im source:	1050	MacAdam Step:	3
W source:	10	Life Time LED 1:	50,000h - L90 - B10 (Ta 25°C)
Luminous efficiency (Im/W, real value):	62.2	Lamp code:	LED
Im in emergency mode:	-	Number of lamps for optical assembly:	1
Total light flux at or above an angle of 90° [Lm]:	0	ZVEI Code:	LED
Light Output Ratio (L.O.R.) [%]:	83	Number of optical assemblies:	2
Beam angle [°]:	48°	Control:	DALI

### Polar

	CIE			
	nL 0.83			
	100-100-100-100-83			
	UGR <10-<10			
	DIN A.61			
	UTE			
	0.83A+0.00T			
	F*1=999			
	F*1+F*2=1000			
	F*1+F*2+F*3=1000			
	CIBSE			
	LG3 L<1500 cd/m² at 65°			
	UGR<10   L<1500 cd/mq @65°			
	Lux			
	h	d	Em	Emax
	2	1.8	323	385
	4	3.6	81	96
	6	5.3	36	43
	8	7.1	20	24

# Utilisation factors

R	77	75	73	71	55	53	33	00	DRR
K0.8	75	71	68	66	70	68	68	65	78
1.0	78	75	72	70	74	72	71	69	83
1.5	82	79	77	76	79	77	76	74	89
2.0	85	83	81	80	82	80	79	77	93
2.5	86	85	84	83	84	83	82	79	96
3.0	87	86	85	85	85	84	83	81	98
4.0	88	87	87	86	86	86	84	82	99
5.0	89	88	88	88	87	86	85	83	100

# UGR diagram

Corrected UGR values (at 1050 lm bare lamp luminous flux)											
Reflect.:		viewed crosswise					viewed endwise				
ceiling/cav		0.70	0.70	0.50	0.50	0.30	0.70	0.70	0.50	0.50	0.30
walls		0.50	0.30	0.50	0.30	0.30	0.50	0.30	0.50	0.30	0.30
work pl.		0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20
Room dim		viewed crosswise					viewed endwise				
x	y										
2H	2H	1.9	2.4	2.2	2.6	2.8	1.9	2.4	2.2	2.6	2.8
	3H	1.8	2.2	2.1	2.5	2.7	1.8	2.2	2.1	2.5	2.7
	4H	1.7	2.1	2.0	2.4	2.7	1.7	2.1	2.0	2.4	2.7
	6H	1.6	2.0	2.0	2.3	2.6	1.6	2.0	2.0	2.3	2.6
	8H	1.6	2.0	2.0	2.3	2.6	1.6	2.0	1.9	2.3	2.6
	12H	1.6	1.9	1.9	2.2	2.6	1.6	1.9	1.9	2.2	2.6
4H	2H	1.7	2.1	2.0	2.4	2.7	1.7	2.1	2.0	2.4	2.7
	3H	1.6	1.9	1.9	2.2	2.6	1.6	1.9	1.9	2.2	2.6
	4H	1.5	1.8	1.9	2.1	2.5	1.5	1.8	1.9	2.1	2.5
	6H	1.4	1.6	1.8	2.0	2.5	1.4	1.6	1.8	2.0	2.5
	8H	1.3	1.6	1.8	2.0	2.4	1.3	1.6	1.8	2.0	2.4
	12H	1.3	1.5	1.7	1.9	2.4	1.3	1.5	1.7	1.9	2.4
8H	4H	1.3	1.6	1.8	2.0	2.4	1.3	1.6	1.8	2.0	2.4
	6H	1.2	1.4	1.7	1.9	2.4	1.2	1.4	1.7	1.9	2.4
	8H	1.2	1.4	1.7	1.8	2.3	1.2	1.4	1.7	1.8	2.3
	12H	1.1	1.3	1.6	1.8	2.3	1.1	1.3	1.6	1.8	2.3
12H	4H	1.3	1.5	1.7	1.9	2.4	1.3	1.5	1.7	1.9	2.4
	6H	1.2	1.4	1.7	1.8	2.3	1.2	1.4	1.7	1.8	2.3
	8H	1.1	1.3	1.6	1.8	2.3	1.1	1.3	1.6	1.8	2.3
Variations with the observer position at spacing:											
S =		0.9 / -18.0					0.9 / -18.0				
		1.5H					9.7 / -18.3				
		2.0H					11.7 / -18.4				