

Last information update: July 2025

**Product configuration: QL81**

QL81: Ø1157mm - Tunable White - Opal - DALI

**Product code**

QL81: Ø1157mm - Tunable White - Opal - DALI

**Technical description**

Round luminaire for ceiling-mounted installation with option of recessed or pendant installation via an accessory to be ordered separately. Up/down emission designed to use Tunable White 2700K÷6500K LED lamps. The optical assembly consists of an extruded painted aluminium frame, a satin finish methacrylate diffuser screen for general light emission and a sheet metal rear closing base. The DALI DT8 driver is housed in the upper part of the product.

**Installation**

Ceiling-mounted. Recessed or pendant-mounted using an accessory to be ordered separately.

**Colour**

White (01) | Black (04)

**Weight (Kg)**

20

**Mounting**

wall surface/ceiling surface

**Wiring**

Product complete with electronic components. The electrical cables used are made of a "halogen free" material. (This means that the cables do not contain any halogen materials that in the event of a fire do not emit toxic or corrosive gases and only a small quantity of opaque fumes).

Complies with EN60598-1 and pertinent regulations

**Technical data**

lm system:	12410	CRI (minimum):	90
W system:	107.2	Colour temperature [K]:	Tunable white 2700 - 6500
lm source:	17000	Life Time LED 1:	50,000h - L90 - B10 (Ta 25°C)
W source:	96	Lamp code:	LED
Luminous efficiency (lm/W, real value):	115.8	Number of lamps for optical assembly:	1
lm in emergency mode:	-	ZVEI Code:	LED
Total light flux at or above an angle of 90° [Lm]:	187	Number of optical assemblies:	1
Light Output Ratio (L.O.R.) [%]:	73	Control:	DALI-2

**Polar**