

Last information update: April 2025

**Product configuration: N124**

N124: wall-washer luminaire - Ø 96 mm - frame



**Product code**

N124: wall-washer luminaire - Ø 96 mm - frame

**Technical description**

Recessed round wall-washer luminaire designed to use a LED lamp with C.O.B. technology. Version with rim for surface-mounting. Reflector vacuum-metallised with aluminium vapours and finished with a protective anti-scratch layer to create a vertical downward beam of light. Die-cast aluminium body and passive dissipation system. Product complete with C.O.B. LED lamp in warm white colour.

**Installation**

Recessed using torsion springs which allow easy installation in false ceilings with thickness ranging from 1 mm to 25 mm.

**Colour**

White / Aluminium (39)

**Weight (Kg)**

0.65

**Mounting**

ceiling recessed


**Wiring**

product complete with DALI components

**Notes**

TPb rated

Complies with EN60598-1 and pertinent regulations



**Technical data**

lm system:	821.35	CRI:	80
W system:	11.9	Colour temperature [K]:	3000
lm source:	1550	MacAdam Step:	2
W source:	9.3	Life Time LED 1:	> 50,000h - L90 - B10 (Ta 25C)
Luminous efficiency (lm/W, real value):	69.02	Lamp code:	LED
lm in emergency mode:	-	Number of lamps for optical assembly:	1
Total light flux at or above an angle of 90° [Lm]:	0.0	ZVEI Code:	LED
Light Output Ratio (L.O.R.) [%]:	53	Number of optical assemblies:	1
Beam angle [°]:	64° / 65°	Control:	DALI-2