


Last information update: May 2024

Product configuration: B582+L160

B582: Projector - 20W HIT (CDM-Tm) - Spot optic

**Product code**B582: Projector - 20W HIT (CDM-Tm) - Spot optic **Attention! Code no longer in production****Technical description**

Projector designed to use metal-halide lamps with spot optic. It is made up of an optical assembly and a component-holding base. The optical assembly, arm, base and frame are made of aluminium alloy EN1706AC 46100LF and are subjected to phosphochromatisation treatment with double primer and passivation at 120 °C. The liquid acrylic paint is baked at 150°C and ensures high resistance to the external environment and UV rays. The hardened soda-lime closing glass (4 mm thick) is transparent and colourless. It is fixed by captive screws. The 50/60 Shore A silicone gasket is subjected to post-cooling treatment (in the oven) in advance for 4/6 hours at 200 °C. The optical assembly can be adjusted both vertically and horizontally. The aiming system can be locked in place and has slots in the frame for rainwater to run off. It is connected to the component box by a silicone armoured cable with protection steel plait. Optic with 99.96% superpure annealed sheet-aluminium reflector subjected to cleanup treatment - 2/4-micron electrochemical anodisation and polishing. The cable clamp for connecting the wiring compartment to the lamp compartment is made of nickel-plated brass M14x1. For power supply, the fitting comes complete with a black polyamide cable clamp PG11 suitable for cables 6.5 to 11.5 mm in diameter. Socket PGJ5 complete with cables. The socket support is made of galvanised steel. All external screws are made of stainless steel A2.

Installation

Application to the ground, wall (by Fischer screws) and tree branches.

Colour

Black (04) | Grey (15)

Mounting

wall surface|ceiling surface

Wiring

Built-in electronic ballast 20W, 220 ÷ 240 V 50 ÷ 60 Hz.

Notes

Accessories available: refractor, wall-washer screens, spike for ground anchoring, belt for branch application, and other installation accessories.

Complies with EN60598-1 and pertinent regulations



960°C

IK08

IP66

**Technical data**

Im system:	822,9	CRI:	86
W system:	23	Colour temperature [K]:	3000
Im source:	1650	Voltage [Vin]:	230
W source:	20	Lamp code:	L160
Luminous efficiency (Im/W, real value):	35,8	Socket:	PGJ5
Im in emergency mode:	-	Number of lamps for optical assembly:	1
Total light flux at or above an angle of 90° [Lm]:	0	ZVEI Code:	HIT-CE
Light Output Ratio (L.O.R.) [%]:	50	Number of optical assemblies:	1
Beam angle [°]:	18°	Intervall temperatura ambiente:	from -20°C to +35°C.

Polar