

Front Light


Design iGuzzini

iGuzzini

Last information update: May 2024

Product configuration: M933+L061

M933: 70W HIT - Flood



Product code

M933: 70W HIT - Flood **Attention! Code no longer in production**

Technical description

Adjustable spotlight with adapter for installation on a mains voltage track. Luminaire made of die-cast aluminium. Spotlight double adjustability allows a 360° rotation about the vertical axis and 90° tilting relative to the horizontal plane. Mechanical aiming locks both for rotation about the vertical axis and tilting relative to the horizontal plane. Equipped with electronic ballast. An external component may be applied, such as directional flaps with 360° rotation and which can be fully closed. Luminaire supplied with flood optic 70W HIT G12. IP 40 on the optical assembly.

Installation

Installation on electrified tracks.

Colour

White (01) | Black (04) | Grey / Black (74)

Weight (Kg)

1.9

Mounting

three circuit track

Wiring

Electronic components for discharge lamp housed in the body

Complies with EN60598-1 and pertinent regulations



IP20



Technical data

lm system: 4564.6

W system: 78

lm source: 6600

W source: 70

Luminous efficiency (lm/W, real value): 58.5

lm in emergency mode: -

Total light flux at or above an angle of 90° [Lm]: 0

Light Output Ratio (L.O.R.) [%]: 69

Beam angle [°]: 28°

CRI: 92

Colour temperature [K]: 4200

Voltage [Vin]: 230

Lamp code: L061

Socket: G12

Number of lamps for optical assembly: 1

ZVEI Code: HIT-CE

Number of optical assemblies: 1

Polar

