



Last information update: October 2023

**Product code**

P526.Y: Fixed circular recessed luminaire - Ø125 mm - warm white - medium optic - UGR<10 - DALI

Technical description

Fixed round luminaire designed to use a LED lamp with C.O.B. technology. Version with rim for surface-mounting. Optic with super comfort reflector vacuum-metallised with aluminium vapours and an anti-scratch protective layer. Die-cast aluminium body and passive dissipation system. Product complete with LED lamp in warm white colour tone CRI90 (3000K). General light emission, with controlled luminance UGR<10 1500 cd/m2 α >65° medium optic.

Installation

Recessed using torsion springs which allow easy installation in false ceilings with thicknesses ranging from 1 mm to 20 mm.

Colour

White / Aluminium (39)

Mounting

ceiling recessed

Wiring

product complete with DALI components

Complies with EN60598-1 and pertinent regulations



IP20

IP54

On the visible part of the product once installed



pending

Technical data

lm system:	1960 (*)	CRI:	90
W system:	30.9 (*)	Colour temperature [K]:	3000
lm source:	2800 (*)	Number of lamps for optical assembly:	1
W source:	28 (*)	ZVEI Code:	LED
Luminous efficiency (lm/W, real value):	63.4 (*)	Number of optical assemblies:	1
lm in emergency mode:	-	Control:	DALI-2
Beam angle [°]:	18° (*)		