


Last information update: July 2025

Product configuration: QL77

QL77: Ø887mm - warm white - Opal - DALI

**Product code**

QL77: Ø887mm - warm white - Opal - DALI

Technical description

Round luminaire for ceiling-mounted installation with option of recessed or pendant installation via an accessory to be ordered separately. Up/down emission designed to use warm white 3000K LED lamps. The optical assembly consists of an extruded painted aluminium frame, a satin finish methacrylate diffuser screen for general light emission and a sheet metal rear closing base. The driver is housed in the upper part of the product.

Installation

Ceiling-mounted. Recessed or pendant-mounted using an accessory to be ordered separately.

Colour

White (01) | Black (04)

Weight (Kg)

12.1

Mounting

wall surface/ceiling surface

Wiring

Product complete with electronic components. The electrical cables used are made of a "halogen free" material. (This means that the cables do not contain any halogen materials that in the event of a fire do not emit toxic or corrosive gases and only a small quantity of opaque fumes).

Complies with EN60598-1 and pertinent regulations

**Technical data**

| | | | |
|--|-------|---------------------------------------|-------------------------------|
| lm system: | 11743 | Colour temperature [K]: | 3000 |
| W system: | 90.8 | MacAdam Step: | 3 |
| lm source: | 15250 | Life Time LED 1: | 50,000h - L90 - B10 (Ta 25°C) |
| W source: | 85 | Lamp code: | LED |
| Luminous efficiency (lm/W, real value): | 129.3 | Number of lamps for optical assembly: | 1 |
| lm in emergency mode: | - | ZVEI Code: | LED |
| Total light flux at or above an angle of 90° [Lm]: | 209 | Number of optical assemblies: | 1 |
| Light Output Ratio (L.O.R.) [%]: | 77 | Control: | DALI-2 |
| CRI (minimum): | 80 | | |

Polar