


Last information update: August 2023

**Product code**MU37: Wall-mounted emergency indication luminaire - LED - Self-Testing **Attention! Code no longer in production****Technical description**

Luminaire with LED lamp for indicating escape routes. Wall-mounted in a parallel cantilever position. White finish, shaped sheet steel component holder structure. Permanent operation (always on - SA); in event of blackouts guarantees an emergency autonomy of 3 hours with the battery fully charged. Sign visible from a distance of 25m (in compliance with UNI EN 1838). Self-test mode. LED warning lamp with function that indicates which devices are operating correctly and if there are any faults. For explanations of all the operating warning lamp functions, see the instructions sheet. Ni-Cd battery with 24 hour recharge time. Indicator screens available with a separate code (pictogram design L22).

Installation

Wall-mounted - by removing the cover safety guard and fixing the support base to the surface using screws and screw anchors (not supplied); the luminaire structure is then mounted on the base.

Colour

White (01)

Mounting

wall surface

Wiring

Inside the structure - the protection panel must be removed and the necessary connections made on the standard terminals.

Notes

Rest Mode function: allows the system to be switched off for short periods. The emergency system must be reactivated using the remote control (code no. MXT0).

Complies with EN60598-1 and pertinent regulations

**Technical data**

lm system:	35 (*)	CRI:	80
W system:	1 (*)	Colour temperature [K]:	4000
lm source:	35 (*)	Number of lamps for optical assembly:	1
W source:	1 (*)	ZVEI Code:	LED
Luminous efficiency (lm/W, real value):	35.0 (*)	Number of optical assemblies:	1
lm in emergency mode:	-		