




Features



- Pendant installation.
- Die-cast aluminium control gear box.
- Die-cast aluminium anchoring base equipped with power cable and hooking device, plus millimetre-accurate adjustment of the steel cable.
- Screen with transparent safety glass housed in a die-cast aluminium ring with a seal.
- Adjustment of light beam opening.



Small body



Large body

Light distribution

Down light
Version with aluminium reflector for down light.



Up/down light
Version with reflector made of glass + aluminium for down/up light.






Diffused lighting
Version with etched glass reflector for diffused light emission. (small body).




	HALO ES	150 - 250W
	HIE	250
	QT 32	150 - 250W


	TC-TEL	42W
	HIT-CE	70 - 150W



light source	W	code	colour
Optical assembly with aluminium reflector			
HALO ES (E27)	150 W max (HALO ES)	4300	78
	250 W (QT 32)		
QT 32 (E27)			
TC-TEL (GX24q-4)	Electronic		
	42 W	4302	78
HIT-CE (G12)	70 W	*4305	78
	150 W	*4306	78
* Complete with safety glass			



Optical assembly with aluminum/glass reflector			
HALO ES (E27)	150 W max (HALO ES)	4332	78
	150/250 W (QT 32)		
QT 32 (E27)			
TC-TEL (GX24q-4)	Electronic		
	42 W	4334	78
HIT-CE (G12)	70 W	*4337	78
	150 W	*4338	78
* Complete with safety glass			



Optical assembly with glass reflector			
QT 32 (E27)	150/250 W	4348	A1
TC-TEL (GX24q-4)	Electronic		
	42 W	4350	A1
HIT-CE (G12)	70 W	*4353	A1
	150 W	*4354	A1
* Complete with safety glass and superpure aluminium flow director			

accessories



	code	colour	code	colour
Kit for ceiling installation and class II connection L=2000	4449	15 for 4300-4302-4305-4306 4332-4334-4337-4338 4348-4350-4353-4354	4449	15 for 4327-4343
Kit for ceiling installation and class II connection L=2000	4447	15 for 4300-4302-4305-4306 4332-4334-4337-4338 4348-4350-4353-4354	4447	15 for 4327-4343
Safety glass complete with seal Use of this accessory guarantees the product IP65 protection	4442	15	---	---
Superpure aluminium flow director	4462	12 for 4350	---	---
Antiglare screen Use of this accessory provides increased visual comfort, but reduces luminous yield.	4450	04 for 4305-4306-4337-4338	4455	04 for 4343
	4451	04 for 4300-4332	4456	04 for 4327