

## Palco Recessed / Surface

Design Artec  
Studio

iGuzzini

Last information update: February 2025

### Product configuration: QX24

QX24: Palco linear surface 2 x Ø19 - medium - remote driver

### Product code

QX24: Palco linear surface 2 x Ø19 - medium - remote driver

### Technical description

Linear luminaire for surface installation with 2 miniaturised adjustable spotlights. Spotlight bodies with a cast zamak dissipation system and rotation units - extruded aluminium linear surface structure - shaped steel fixing plate - extruded aluminium linear surface structure with mechanical coupling system - thermoplastic side end caps. The spotlight swivel joints allow the spotlight to be rotated by 360° and tilted by 90°. The set back position of the optic units guarantees a high level of visual comfort with thermoplastic high definition lenses. Ballast not included, available with separate code.

### Installation

Installation surface plate fastening - structure attached using a mechanical locking mechanism - insertion of side end caps. This specific locking system can be installed next to linear versions so as to create a continuous external line.

### Colour

White (01) | Black (04)

### Weight (Kg)

0.18


### Mounting

wall surface|ceiling surface

### Wiring

Output cables for connecting to power supply line.

Complies with EN60598-1 and pertinent regulations



### Technical data

lm system:	308	CRI (minimum):	90
W system:	4	Colour temperature [K]:	4000
lm source:	230	MacAdam Step:	2
W source:	2	Life Time LED 1:	> 50,000h - L80 - B10 (Ta 25°C)
Luminous efficiency (lm/W, real value):	77.1	Lamp code:	LED
lm in emergency mode:	-	Number of lamps for optical assembly:	1
Total light flux at or above an angle of 90° [Lm]:	0	ZVEI Code:	LED
Light Output Ratio (L.O.R.) [%]:	67	Number of optical assemblies:	2
Beam angle [°]:	24°	LED current [mA]:	700

### Polar

Imax=799 cd	Lux			
	h	d	Em	E <sub>max</sub>
	1	0.4	656	799
	2	0.8	164	200
	3	1.3	73	89
	4	1.7	41	50