

Design iGuzzini iGuzzini

Product configuration: EQ50.15

Product code

Technical description

Installation

Colour
Grey (15)

Weight (Kg)
6.05

Mounting

wall arm|pole-top

Notes

Complies with EN60598-1 and pertinent regulations



Technical data

| | | | |
|----------------------------------------------------|--------------------------------|--------------------------------------------------------------------------|-----------------------------------------------------------------------------------------|
| Im system: | 11970 | Voltage [Vin]: | 230 |
| W system: | 87.6 | Lamp code: | LED |
| Im source: | - | Number of lamps for optical assembly: | 1 |
| W source: | - | ZVEI Code: | LED |
| Luminous efficiency (Im/W, real value): | 136.6 | Number of optical assemblies: | 1 |
| Im in emergency mode: | - | Intervallo temperatura ambiente: | from -40°C to 35°C. |
| Total light flux at or above an angle of 90° [Lm]: | 0 | Power factor: | See installation instructions |
| Light Output Ratio (L.O.R.) [%]: | 100 | Inrush current: | 41.6 A / - μs |
| CRI (minimum): | 70 | Maximum number of luminaires of this type per miniature circuit breaker: | B10A: 6 luminaires B16A: 10 luminaires C10A: 10 luminaires C16A: 17 luminaires |
| Colour temperature [K]: | 3000 | Minimum dimming %: | 5 |
| MacAdam Step: | 3 | Overvoltage protection: | 10kV Common mode & 6kV Differential mode |
| Life Time LED 1: | 100,000h - L90 - B10 (Ta 25°C) | Control: | Midnight preset/DALI NFC |

Polar

