iGuzzini

Last information update: October 2024

Product configuration: QR30

QR30: Minimal sections 2 x 5 LEDs - Wall Washer - LGC





QR30: Minimal sections 2 x 5 LEDs - Wall Washer - LGC

Technical description

Linear recessed miniaturised luminaire for LED lamps, specialised for vertical wall lighting. The patented optic system guarantees a homogeneous and effective emission on the wall, as well as avoiding shadow zones near the ceiling. The black polycarbonate perimeter frame is designed to significantly reduce the effect of longitudinal glare while also guaranteeing maximum light uniformity on the wall. Main body with die-cast aluminium radiant surface, minimal (frameless) version for mounting flush with the ceiling. For recessed installation in a false ceiling a specific adapter is required that is available with a separate item code. Flux enhancer superpure aluminium reflector - asymmetrical textured PMMA screen.

Installation

The recess body is inserted in the specific adapter installed previously by means of a steel wire spring - check the thickness of the false ceiling and use a compatible frame available with a separate item code.

Colour

Black (04)

Mounting

wall recessed|ceiling recessed







On the visible part of the product once installed



8



NOM:


Complies with EN60598-1 and pertinent regulations

265 [5] <u>_</u>/ 33x270

26

Technical data			
Im system:	527	CRI (typical):	97
W system:	21	Colour temperature [K]:	2700
Im source:	1700	MacAdam Step:	3
W source:	21	Life Time LED 1:	50,000h - L90 - B10 (Ta 25°C)
Luminous efficiency (lm/W, real value):	25.1	Lamp code:	LED
		Number of lamps for optical	1
Im in emergency mode:	-	assembly:	
Total light flux at or above an angle of 90° [Lm]:	0	ZVEI Code:	LED
		Number of optical	1
Light Output Ratio (L.O.R.) [%]:		assemblies:	
		LED current [mA]:	700
CRI (minimum):	95		





Illuminances

