


Last information update: May 2024

**Product configuration: QB34**

QB34: Angular LED module - Frame Down HO - ON-OFF - General Light - Warm

**Product code**QB34: Angular LED module - Frame Down HO - ON-OFF - General Light - Warm **Attention! Code no longer in production****Technical description**

Angular element for Frame version profiles with contact frame; including a 3000K Warm LED module, High Output version. The module optic and structural fittings allow high luminous flux and system efficiency values. Methacrylate opal screen for diffused general light; screen set up for overlap connections. Integrated control gear. Pass-through wiring for continuous lines:

**Installation**

Recessed using the brackets on the profile.

**Colour**

White (01)

**Weight (Kg)**

4.17

**Mounting**

ceiling recessed

**Wiring**

The angular profile is supplied with pass-through wiring for continuous lines. Quick coupling terminal blocks to simplify connections between the luminaires. Complete with integrated ON-OFF - non-dimmable control gear.

**Notes**

Take care when configuring the system; to complete a continuous line with an angular profile correctly, two initial modules are required, one for each end of the corner.

Complies with EN60598-1 and pertinent regulations

**Technical data**

|  |       |                                       |                                 |
|--|-------|---------------------------------------|---------------------------------|
| Im system:   | 2964  | CRI:                                  | 80                              |
| W system:  | 24.6  | Colour temperature [K]:               | 3000                            |
| Im source:   | 1950  | MacAdam Step:                         | 3                               |
| W source:  | 11    | Life Time LED 1:                      | > 50,000h - L90 - B10 (Ta 25°C) |
| Luminous efficiency (Im/W, real value):            | 120.5 | Lamp code:                            | LED                             |
| Im in emergency mode:                              | -     | Number of lamps for optical assembly: | 1                               |
| Total light flux at or above an angle of 90° [Lm]: | 0     | ZVEI Code:                            | LED                             |
| Light Output Ratio (L.O.R.) [%]:                   | 76    | Number of optical assemblies:         | 2                               |

**Polar**