


Last information update: October 2024

**Product configuration: BJ38**

BJ38: Wall-/Ceiling-mounted - 12 Warm White LEDs - 24V/500mA dc - L=1056mm - Wall Grazing Optic

**Product code**

BJ38: Wall-/Ceiling-mounted - 12 Warm White LEDs - 24V/500mA dc - L=1056mm - Wall Grazing Optic

**Technical description**

Direct light luminaire, designed to use monochrome LED lamps. Ceiling- and wall-mounted. Consists of a body and supports for installation (to be ordered separately). Extruded aluminium body, with zamak die-cast end caps complete with silicone seals. Coated with liquid acrylic paint with a high level of weather and UV ray resistance. The top of the optical assembly is closed by a 3 mm thick transparent glass screen, fixed with silicone. Complete with multi-LED power plate in Warm White 3000K with 24V/500mA dc electronic circuit (power supply to be ordered separately); 24V/500mA smart driver allowing constant light flow emission despite variations in the input voltage (from 30V dc to 16V dc). Fitted with a PMMA diffusing filter and optic with plastic (methacrylate) lens for Wall Grazing lighting. All external screws used are made of A2 stainless steel. The luminaire technical characteristics conform to EN 60598-1 standards and particular requirements.

**Installation**

The following accessories are available for installation: adjustable wall-mounted arms in AISI304 stainless steel (L=83mm code BZJ9, 200mm code BZJ8) and a plate for surface- or ceiling-mounting made of anodised aluminium (BZJ6).

**Colour**

Grey (15)

**Weight (Kg)**

1.59

**Mounting**

wall surface|ceiling surface

**Wiring**

The product is supplied with a single nickel-plated brass cable gland PG9 and a 2x1mm<sup>2</sup> PVC and polyurethane outlet cable, 2000mm long. For the electrical connection there is an IP68 linear connector (BZK6) and an IP66 junction box with quick-coupling terminals (BZK7). 24V/500mA dc electronic ballasts to be ordered separately: 32W (BZA0), 25W (K980) and 35W (BZM4)

**Notes**

Product complete with LED lamp.

Complies with EN60598-1 and pertinent regulations




IK05

IP66

**Technical data**

Im system:	779	MacAdam Step:	3
W system:	19	Life Time LED 1:	66,000h - L80 - B10 (Ta 25°C)
Im source:	1440	Life Time LED 2:	66,000h - L80 - B10 (Ta 40°C)
W source:	19	Lamp code:	LED
Luminous efficiency (Im/W, real value):	41	Number of lamps for optical assembly:	1
Im in emergency mode:	-	ZVEI Code:	LED
Total light flux at or above an angle of 90° [Lm]:	0	Number of optical assemblies:	1
Light Output Ratio (L.O.R.) [%]:	54	Intervallo temperatura ambiente:	from -30°C to 50°C.
CRI (minimum):	80	LED current [mA]:	500
Colour temperature [K]:	3000		

Polar



Illuminances

Lux		Wall distance = 1m															
3																	
		0.1	0.2	0.6	2	4	6	4	2	0.7	0.3	0.1					
2		0.7	1	3	6	10	14	12	7	3	2	0.8					
		1	2	4	8	13	16	15	9	5	3	1					
1		2	3	5	9	13	17	15	9	5	3	2					
		2	3	5	8	12	15	13	9	5	3	2					
0																	
	m	-2	-1	0	1	2	3										