

Blade R downlight

Design iGuzzini

iGuzzini

Last information update: February 2025

Product configuration: R446

R446: accessory cover wall-mounted wall washer light



Product code

R446: accessory cover wall-mounted wall washer light

Technical description

Round fixed luminaire designed to use LED lamps with C.o.B. technology. Version compatible with Ø170 mm Blade R (18 LEDs) complete with device for coupling it to the luminaire and DALI control gear with a DT6 control system. Reflector vacuum-metallised with aluminium vapours with an anti-scratch protective layer. Dissipater made of painted grey die-cast aluminium. Product complete with warm white tone (3000K) LED. Wall Washer emission for effective wall lighting combined with the main recessed lighting feature.

Installation

Downlight accessory for Ø170 mm Blade R (18 LEDs)

Colour

White / Aluminium (39) | Black / Aluminium (40)

Weight (Kg)

0.34

Mounting

ceiling surface



Complies with EN60598-1 and pertinent regulations



IP20

IP23

On the visible part of the product once installed



Technical data

lm system:	1178.0	CRI:	90
W system:	12.8	Colour temperature [K]:	3000
lm source:	1550	MacAdam Step:	2
W source:	11	Life Time LED 1:	> 50,000h - L90 - B10 (Ta 25C)
Luminous efficiency (lm/W, real value):	92.03	Lamp code:	LED
lm in emergency mode:	-	Number of lamps for optical assembly:	1
Total light flux at or above an angle of 90° [Lm]:	0.0	ZVEI Code:	LED
Light Output Ratio (L.O.R.) [%]:	76	Number of optical assemblies:	1
Beam angle [°]:	67° / 70°	Control:	DALI-2