

Cylindrical pole

Last information update: February 2024



Accessory code


1518: Pole for burial L=6800 diam. 102mm cylindrical shank ø76mm

Technical description

Cylindrical pole made of 70 micron hot galvanised steel, in compliance with UNI EN ISO 1461 (EN 40-5), subsequently surface treated with textured acrylic powder paint (grey/black). The standard painting cycle refers to the UNI EN ISO 12944 standard with durability class C4-H (suitable for industrial areas and coastal zones with moderate salinity). The UNI EN ISO 12944-1 standard specifies routine maintenance and 6-monthly checks to conserve the product intact. The pole consists of a single welded tube with a cylindrical shank ø76mm, L=106 mm at the top. It is made of EN10025-S235JR (ex Fe360 UNI7070) steel, 102 mm in diameter, 3 mm thick and 6800 mm high (6000 mm from the ground). The slot for the access cover measures 186x45 mm, at a height of 1000 mm from the ground, suitable for fitting the terminal block with one fuse (code 1862) or two fuses (code 1865). External access cover made of GDALSI 12 aluminium alloy

Installation

The pole is designed for burial, with the buried part measuring 800 mm. To protect the pole, a corrosion-resistant protective sheath can be applied to the area in contact with the ground. The sheath is not included with the pole accessories. Upon request, a pole base plate can be used (code 1850), consisting of two parts which can be joined together, made of die-cast aluminium, 420 mm in diameter and 122 mm high.



Colour

Grey (15)

Weight (Kg)

51

Wiring

The electric power cable enters through the slot located 350 mm from the base of the metal cylinder, and measures 150x50 mm. The pole has a hole for securing the earthing lug, designed to accommodate the external earth cable. It is located 70 mm from the ground, is 11 mm in diameter, and is secured using M8x17 mm A2 stainless steel screws.

Complies with EN60598-1 and pertinent regulations

