

Reflex

iGuzzini

iGuzzini

Last information update: April 2024

Product configuration: N225
N225: Fixed circular recessed luminaire - Ø212 mm - warm white - flood optic - UGR<19

N225: Fixed circular recessed luminaire - Ø212 mm - warm white - flood optic - UGR<19

N225: Fixed circular recessed luminaire - Ø212 mm - warm white - flood optic - UGR<19 **Attention! Code no longer in production**

Fixed round luminaire designed to use a LED lamp with C.O.B. technology. Version with rim for surface-mounting. Reflector vacuum-metallised with aluminium vapours with an anti-scratch protective layer. Die-cast aluminium body and passive dissipation system. Product complete with LED lamp in warm white colour tone (3000K). General light emission, with controlled luminance UGR<19 1500 cd/m2 α >65° flood optic.


Recessed using torsion springs which allow easy installation in false ceilings with thickness ranging from 1 mm to 25 mm.

Colour	Weight (Kg)
White / Aluminium (39)	1.95

ceiling recessed

product complete with an electronic ballast

 IP20 IP54



Technical data		CRI (minimum): 80	
lm system:	4378	Colour temperature [K]: 3000	
W system:	36.4	MacAdam Step: 2	
lm source:	5150	Life Time LED 1: > 50,000h - L80 - B10 (Ta 25°C)	
W source:	32	Lamp code: LED	
Luminous efficiency (lm/W, real value):	120.3	Number of lamps for optical assembly: 1	
lm in emergency mode:	-	ZVEI Code: LED	
Total light flux at or above an angle of 90° [Lm]:	0	Number of optical assemblies: 1	
Light Output Ratio (L.O.R.) [%]:	85		
Beam angle [°]:	26°		

--

Utilisation factors

R	77	75	73	71	55	53	33	00	DRR
K0.8	77	73	70	68	72	70	69	67	78
1.0	80	77	74	72	76	74	73	71	83
1.5	84	81	79	78	80	79	78	75	89
2.0	87	85	83	82	84	82	81	79	93
2.5	88	87	86	85	86	85	84	81	96
3.0	89	88	87	87	87	86	85	83	98
4.0	90	90	89	89	88	88	87	84	99
5.0	91	90	90	90	89	89	87	85	100

UGR diagram

Corrected UGR values (at 5150 lm bare lamp luminous flux)											
Reflect.:		viewed crosswise					viewed endwise				
ceiling		0.70	0.70	0.50	0.50	0.30	0.70	0.70	0.50	0.50	0.30
walls		0.50	0.30	0.50	0.30	0.30	0.50	0.30	0.50	0.30	0.30
work pl.		0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20
Room dim											
x	y										
2H	2H	12.6	14.6	13.0	14.9	15.2	12.6	14.6	13.0	14.9	15.2
	3H	12.5	13.9	12.9	14.2	14.6	12.5	13.9	12.9	14.2	14.6
	4H	12.4	13.7	12.8	14.0	14.3	12.4	13.7	12.8	14.0	14.3
	6H	12.4	13.4	12.7	13.8	14.1	12.4	13.4	12.7	13.8	14.1
	8H	12.3	13.4	12.7	13.7	14.1	12.3	13.4	12.7	13.7	14.1
	12H	12.3	13.3	12.7	13.7	14.0	12.3	13.3	12.7	13.7	14.0
4H	2H	12.4	13.7	12.8	14.0	14.3	12.4	13.7	12.8	14.0	14.3
	3H	12.3	13.3	12.7	13.7	14.0	12.3	13.3	12.7	13.7	14.0
	4H	12.1	13.1	12.6	13.5	13.9	12.1	13.1	12.6	13.5	13.9
	6H	11.9	13.3	12.3	13.7	14.2	11.9	13.3	12.3	13.7	14.2
	8H	11.7	13.4	12.2	13.8	14.3	11.7	13.4	12.2	13.8	14.3
	12H	11.6	13.4	12.1	13.9	14.4	11.6	13.4	12.1	13.9	14.4
8H	4H	11.7	13.4	12.2	13.8	14.3	11.7	13.4	12.2	13.8	14.3
	6H	11.6	13.2	12.1	13.7	14.2	11.6	13.2	12.1	13.7	14.2
	8H	11.6	13.0	12.1	13.5	14.0	11.6	13.0	12.1	13.5	14.0
	12H	11.7	12.7	12.2	13.2	13.7	11.7	12.7	12.2	13.2	13.7
12H	4H	11.6	13.4	12.1	13.9	14.4	11.6	13.4	12.1	13.9	14.4
	6H	11.6	13.0	12.1	13.5	14.0	11.6	13.0	12.1	13.5	14.0
	8H	11.7	12.7	12.2	13.2	13.7	11.7	12.7	12.2	13.2	13.7
Variations with the observer position at spacing:											
S =		1.0H	6.7 / -31.5				6.7 / -31.5				
		1.5H	9.5 / -31.8				9.5 / -31.8				
		2.0H	11.5 / -32.1				11.5 / -32.1				