# Reflex

Design iGuzzini

iGuzzini

Last information update: April 2024

### **Product configuration: MB71**

MB71: Round recessed luminaire - D=226 mm H=103 mm - LED warm white - DALI ballast - optic with asymmetrical double emission



## Product code

MB71: Round recessed luminaire - D=226 mm H=103 mm - LED warm white - DALI ballast - optic with asymmetrical double emission Attention! Code no longer in production

### **Technical description**

Recessed fixed round luminaire designed to use a LED lamp. Version with rim for surface-mounting. Reflector vacuum-metallised with aluminium vapours with an anti-scratch protective layer. Die-cast aluminium body and passive dissipation system. Product complete with 2000 lm DALI LED unit in a warm tone 3000K and driver separate from the luminaire. Double asymmetrical light

### Installation

Recessed using torsion springs which allow easy installation in false ceilings with thickness ranging from 1 mm to 25 mm.

Colour Weight (Kg) White / Aluminium (39) 1.72




ceiling recessed

# Wiring

Product complete with DALI electronic components


IP23

Complies with EN60598-1 and pertinent regulations CE IP20



To also to all dese			
Technical data			
Im system:	1879	Colour temperature [K]:	3000
W system:	21	MacAdam Step:	3
Im source:	2000	Life Time LED 1:	50,000h - L80 - B10 (Ta 25°C)
W source:	18	Lamp code:	LED
Luminous efficiency (lm/W, real value):	89.5	Number of lamps for optical assembly:	1
Im in emergency mode:	-	ZVEI Code:	LED
Total light flux at or above an angle of 90° [Lm]:	0	Number of optical assemblies:	1
Light Output Ratio (L.O.R.) [%]:	94	Control:	DALI
CRI:	80		





# Lux h=5 m. α=0° LED / 21W

