Design iGuzzini

iGuzzini

Last information update: June 2025

#### Product configuration: QY81.00

QY81.00: LED STRIP for Superrail LV track - L 300 - 4.4W 464.4lm - 2700K - CRI 90 - Indeterminate



#### **Product code**

QY81.00: LED STRIP for Superrail LV track - L 300 - 4.4W 464.4lm - 2700K - CRI 90 - Indeterminate

### Technical description

Linear lighting product - with white monochrome LEDs - on a flexible white circuit coated with a layer of silicone and complete with adapter for installation on a Superrail LV track. One end of the circuit is fitted with a connector for connecting it to the adapter. The connector has an IP20 protection rating, therefore we recommend that the strips are used indoors. The adapter made of a thermoplastic material includes the DC/DC driver circuit with a DALI dimmable function. Integrated «power line» technology allows each light module on the track to be adjusted separately. LED specifications: 2700 K warm white colour - 70 LEDs/m - 120° flare angle - 48V power supply. Ballasts to be ordered separately

#### Installation

The device can be secured mechanically using either an adapter or a silicone sheath.

 Colour
 Weight (Kg)

 White (01) | Black (04)
 0.03

#### Mounting

Low voltage track

## Wiring

Integrated DC/DC LED driver in adapter - direct connection on Superrail LV track. Track power supply unit to be ordered separately.

Complies with EN60598-1 and pertinent regulations



IP20













#### **Technical data**

Im system:	464	MacAdam Step:	3	
W system:	4.4	Life Time LED 1:	> 50,000h - L90 - B10 (Ta 25°C)	
Im source:	540	Lamp code:	LED	
W source:	3.4	Number of lamps for optical	1	
Luminous efficiency (Im/W,	105.5	assembly:		
real value):		ZVEI Code:	LED	
Im in emergency mode:	-	Number of optical	1	
Total light flux at or above	464	assemblies:		
an angle of 90° [Lm]:		LED current [mA]:	59	
Light Output Ratio (L.O.R.) [%]:	86	Power factor:	See installation instructions	
		Minimum dimming %:	5	
CRI (minimum):	90	Overvoltage protection:	2kV Common mode & 1kV Differential mode	
Rf (Colour Fidelity Index):	91			
Rg (Gamut Index):	97	Control:	DALI	
Colour temperature [K]:	2700			

# Polar

lmax=177 cd	Lux			
180°	h	d	Em	Emax
	1	2.8	104	177
	2	5.7	26	44
90° 90°	3	8.5	12	20
150 α=110°	4	11.4	6	11