


Last information update: October 2024



Product code

2406: Minimal 1 cell - Flood - LED

Technical description

Square miniaturised recessed luminaire for a single LED lamp - fixed optic. Die-cast aluminium body, minimal version (frameless) installed flush with ceiling. For recessed installation in a false ceiling a specific adapter is required that is available with a separate item code. Metallised, thermoplastic, high definition OptiBeam reflector, integrated in a set-back position in the anti-glare screen. Connecting cable supplied. Ballast not included, available with separate code.

Installation

The recess body is inserted in the specific adapter installed previously by means of a steel wire spring - check the thickness of the false ceiling and use a compatible frame available with a separate item code.

Colour


White (01) | Black (04)

Mounting


wall recessed|ceiling recessed|ceiling surface

Wiring

Constant current ballasts to be ordered separately: ON-OFF - code no. MXF9; DALI dimmable - code no. BZM4 - check the instruction sheet for the operating current setting and the compatible length and cross sections of the cables to be used.



Complies with EN60598-1 and pertinent regulations



Technical data

lm system:	188 (*)	Beam angle [°]:	32 (*)
W system:	2.1 (*)	CRI:	90
lm source:	227 (*)	Colour temperature [K]:	3500
W source:	2.1 (*)	Number of lamps for optical assembly:	1
Luminous efficiency (lm/W, real value):	89.52 (*)	ZVEI Code:	LED
lm in emergency mode:	-	Number of optical assemblies:	1