

Sistema Easy MH
page 115



General light



Wall Washer

ø 212



Sistema Easy FL
page 117



General light

Sistema Easy FL
page 117



General light

ø 212



ø 250






Features




- Recessed installation in false ceilings with 1 to 25 mm thickness.
- Die-cast aluminium body and heat sink.
- Mirror aluminium ultrapure reflectors with high luminous efficiency.
- Luminaire reduced height h=115mm.
- The minimum sizes of the installation compartment are displayed in the instructions sheet available on the online catalogue.
- IP20
- IP23 for visible body of fitting after installation.



Rapid installation




Quick-connecting terminal




Two-part reflector (for general light version)

Light distribution




General lighting

This optic with high performance reflector guarantees high level light output, reducing lighting system costs.



General light with diffuser glass

This version provides shadow-free diffused light, for uniform lighting without luminance contrast.







Wall Washer

The asymmetrical distribution of the beam of light allows uniform wall lighting, extending system lighting design flexibility.

HIT-DE-CE 70 - 150W



light source		W	code	colour	light source		W	code	colour		
	HIT-DE-CE (Rx7s)	General lighting					HIT-DE-CE (Rx7s)	Wall washer			
		High-efficiency reflector complete with safety glass									
		70 W		3927	39			70 W		4663	39
		150 W		3928	39			150 W		4664	39
		Diffusing glass									
		70 W		3929	39						
		150 W		3930	39						

accessories

	code	colour
 Reinforcement plate for false ceilings	6024	00
 Casing for concrete ceilings	6029	00 for 3927-3929-4663


components

	code	colour
 Electronic control gear for 70 W HIT Kg. 0,350 - Dim. 185x90x37h	4467	00
 for 150 W HIT Kg. 0,350 - Dim. 185x90x37h	4465	00
 Control gear complete with capacitor for 70 W HIT Kg. 1,700 - Dim. 257x92x70h	4469	00
 for 150 W HIT Kg. 2,550 - Dim. 332x110x77h	4470	00
 Control gear complete with capacitor and ignitor with controlled pulses for 70 W HIT Kg. 1,700 - Dim. 257x92x70h	4472	00
 for 150 W HIT Kg. 2,550 - Dim. 332x110x77h	4473	00



Features

- Recessed installation in false ceilings with 1 to 25 mm thickness.
- Self-extinguishing thermoplastic body and painted sheet steel heat sink.
- Reflecting surface, 2 different finishes: high luminous efficiency specular metallized and matt.
- Available with electronic, multiwatt electronic and DALI control gear and emergency light with inverter.
- Dimmable DALI models are equipped with a Switch Dim, which allows the user to adjust the light with a standard electric switch.
- Luminaire reduced height h=100 mm.
- The minimum sizes of the installation compartment are displayed in the instructions sheet available on the online catalogue.
- IP20
- IP23 for visible body of fitting after installation.



Rapid installation



Large rim



Lamp centring device

Light distribution

Metallized reflector
High output and controlled emission make this reflector ideal for all public areas, even large ones.



	TC-TEL	2x14/17W
	TC-DEL	18 - 26 - 2x13W
		2x18 - 2x26W
	TC-TEL	32 - 42W
		2x26/32/42W

Reflectors

Dark-light reflector
UGR<19



Can be fitted on reflector
with metallised finish



Reflector for
downlight
Wall Washer effect



Can be fitted on reflector
with metallised finish



Decorative screens

Tapered
decorative



Decorative
cylindrical



Use of these accessories
guarantees IP44
degree of protection



Decorative
glass



Screens

Transparent
screen



Diffuser screen



Diffusing
central part



Customisation rims

Customisation
rim



Indicator
screen



Use of these accessories
guarantees IP44
degree of protection



With transparent
screen



With diffuser
screen






With diffusing
central part



Use of these accessories
guarantees IP44
degree of protection





light source		W	code colour		
  ø 232 ø 212	Metallized reflector Complete with control gear				
	Electronic				
	18 W	3300	39		
	26 W	3301	39		
	2x18 W	3303	39		
	2x26 W	3304	39		
	DALI				
	18 W	3343	39		
	26 W	3344	39		
	2x18 W	3345	39		
	2x26 W	3346	39		
	Inductive with inverter				
	2x18 W	3359	39		
	2x26 W	3360	39		
  ø 232 ø 212	Metallized reflector Complete with control gear				
	Electronic				
	32 W	3305	39		
	42 W	3595	39		
	2x32 W	3306	39		
	DALI				
	32 W	3347	39		
	42 W	3348	39		
	2x32 W	3349	39		
	DALI versions (class of insulation I) occupy 1 DALI address.				
	  232 212x212	Metallized reflector Complete with control gear			
		Electronic			
		18 W	3864	39	
		26 W	3865	39	
2x18 W		3867	39		
2x26 W		3868	39		
DALI					
18 W		3907	39		
26 W		3908	39		
2x18 W		3909	39		
2x26 W		3910	39		
Inductive with inverter					
2x18 W		3923	39		
2x26 W		3924	39		
DALI versions (class of insulation I) occupy 1 DALI address.					
  232 212x212	Metallized reflector Complete with control gear				
	Electronic				
	32 W	3305	39		
	42 W	3595	39		
	2x32 W	3306	39		
	DALI				
	32 W	3347	39		
	42 W	3348	39		
	2x32 W	3349	39		
	DALI versions (class of insulation I) occupy 1 DALI address.				
	  270 250x250	Metallized reflector Complete with control gear			
		Electronic			
		2x26/32/42 W	6283	39	
		DALI			
2x26/32/42 W		6289	39		
DALI					
2x26/32/42 W		6289	39		
DALI versions (class of insulation I) occupy 1 DALI address.					

Sistema Easy FL

accessories		 212		 250		 212x212		 250x250		
		code	colour	code	colour		code	colour	code	colour
	Dark-light reflector UGR<19	6926	12 for version with metallized reflector	9676	12		6930	12 for version with metallized reflector	9677	12
	Reflector for downlight wall washer effect	6095	12 for version with metallized reflector	---	---		6096	12 for version with metallized reflector	---	---
	Transparent screen IP44	6016	24	9613	24		6020	24	9616	24
	Diffuser screen IP44	6017	65	9614	65		6021	65	9617	65
	Protection screen with diffusing central part IP44	6035	B7	9615	B7		6036	B7	9618	B7
	Customisation rim It cannot be installed in combination with diffusers	6037	15	---	---		6042	15	---	---
	Customisation rim complete with transparent protection screen IP44						6043	B6	---	---
	grey customisation rim	6038	B6	---	---					
	white customisation rim	6039	D8	---	---		6044	A1	---	---
	Customisation rim complete with diffusing protection screen IP44	6040	A1	---	---					
	Customisation rim complete with diffusing protection screen IP44	6041	A1	---	---		6045	A1	---	---
	Decorative glass	6046	A1-D9	---	---		6025	00	---	---
	Reinforcement plate for false ceilings	6024	00	---	---		6031	00 no for 3923-3924	---	---
	Casing for concrete ceilings	6029	00 no for 3284-3290 3359-3360	---	---					