iGuzzini

Last information update: January 2025

Product configuration: PS02

PS02: Dimmable electronic Ø102mm body - Medium optic



Product code

PS02: Dimmable electronic Ø102mm body - Medium optic

Technical description

Adjustable spotlight with adapter for installation on an electrified track or base. High chromatic yield LED lamp with 3500K tone and OptiBeam Lens optic system and Medium optic. Dimmable electronic power supply integrated in product with Tool Free manual dimmer. Luminaire made of die-cast aluminium and thermoplastic material that allows a 360° rotation about the vertical axis and 90° tilting relative to the horizontal plane with mechanical aiming locks. Passive heat dissipation. Spotlight with "Push&Go" system designed to hold up to two flat accessories at the same time. The same system can also be used to apply another external component selected from the directional flaps and anti-glare screen. All internal accessories rotate 360° about the spotlight longitudinal axis.

Installation

Installation on an electrified track or base.

Colour White (01) | Black (04) Weight (Kg)

1.33



wall surface|ceiling surface

Wiring

Electronic components integrated in product

Complies with EN60598-1 and pertinent regulations

> 50,000h - L90 - B10 (Ta 25°C)






















Technical data Im system: W system:

Im source:

1651 19.9 1920 18

W source: Luminous efficiency (lm/W, 83 real value): Im in emergency mode: Total light flux at or above

an angle of 90° [Lm]: Light Output Ratio (L.O.R.) 86 [%]:

Beam angle [°]: 16° CRI (minimum): 97 Colour temperature [K]: 3500

MacAdam Step: 2 Life Time LED 1: Lamp code:

Number of lamps for optical 1 assembly: ZVEI Code: Number of optical assemblies:

See installation instructions Power factor: Inrush current: 5~A / $50~\mu\text{s}$

LED

Maximum number of luminaires of this type per

Control:

B10A: 31 luminaires B16A: 50 luminaires miniature circuit breaker: C10A: 52 luminaires C16A: 85 luminaires

Minimum dimming %:

Overvoltage protection: 4kV Common mode & 2kV Differential mode

Completo di dimmer

Polar

Imax=13821 cd	Lux			
90° 180° 90°	h	d	Em	Emax
	2	0.6	2725	3455
	4	1.1	681	864
15000	6	1.7	303	384
α=16°	8	2.3	170	216