


Last information update: May 2024

Product configuration: BY86

BY86: Camberra - Pole-mounted system for urban and residential parks and gardens

**Product code**BY86: Camberra - Pole-mounted system for urban and residential parks and gardens **Attention! Code no longer in production****Technical description**

Outdoor luminaire with an elliptical optic, designed to use LED lamps. The optical assembly and the pole attachment system are made of EN1706AC 46100LF aluminium alloy and subjected to a multi-step, pre-treatment process, in which the main phases are degreasing, fluorozirconation (a protective surface film) and sealing (with a nano-structured silane layer). The painting stage consists of a primer and a liquid acrylic paint, cured at 150 °C, with a high level of weather and UV ray resistance. Diffusor made of shockproof, UV-stabilised injection moulded polycarbonate. Complete with circuit fitted with Neutral White monochrome LEDs. Optical assembly consisting of an anodized super-pure aluminium upper reflector, a methacrylate lens and a lower reflector made of metallised PC. Replaceable LEDs and driver. Electronic selv driver with automatic internal temperature control system. Overvoltage protection up to 9KV. All external screws are made of stainless steel.

Installation

The luminaire can be installed with a pole-top mounting on poles with \varnothing 60mm and 76mm end part using X102 and X126 accessories. Secured to the pole by two bolts.

Colour

Grey (15)

Mounting

pole-top


Wiring

The product is supplied wired and with an outlet cable (2x1mm) 500mm long.

Complies with EN60598-1 and pertinent regulations

**Technical data**

Im system:	2160	MacAdam Step:	2
W system:	20	Life Time LED 1:	59,000h - L90 - B10 (Ta 25°C)
Im source:	-	Life Time LED 2:	100,000h - L80 - B10 (Ta 25°C)
W source:	-	Life Time LED 3:	34,000h - L90 - B10 (Ta 40°C)
Luminous efficiency (lm/W, 108 real value):		Life Time LED 4:	100,000h - L80 - B10 (Ta 40°C)
Im in emergency mode:	-	Lamp code:	LED
Total light flux at or above an angle of 90° [Lm]:	58	Number of lamps for optical assembly:	1
Light Output Ratio (L.O.R.) [%]:	100	ZVEI Code:	LED
Beam angle [°]:	148° / 88°	Number of optical assemblies:	1
CRI:	80	Intervallo temperatura ambiente:	from -20°C to +35°C.
Colour temperature [K]:	4000	Control:	On/off

Polar

Isolux

