

Last information update: April 2025

**Product configuration: MN04**

MN04: wall-washer luminaire - Ø 212 mm - warm white - frame



**Product code**

MN04: wall-washer luminaire - Ø 212 mm - warm white - frame

**Technical description**

Recessed round wall-washer luminaire designed to use a LED lamp with C.O.B. technology. Version with rim for surface-mounting. Reflector vacuum-metallised with aluminium vapours and finished with a protective anti-scratch layer to create a vertical downward beam of light. Die-cast aluminium body and passive dissipation system. Product complete with C.O.B. LED lamp in warm white colour tone 3000K.

**Installation**

Recessed using torsion springs which allow easy installation in false ceilings with thickness ranging from 1 mm to 25 mm

**Colour**

White / Aluminium (39)

**Weight (Kg)**

2.87

**Mounting**

ceiling recessed

**Wiring**

Product complete with DALI components


**Notes**

TPb rated

Complies with EN60598-1 and pertinent regulations



On the visible part of the product once installed



**Technical data**

Im system:	3338.47	Life Time LED 1:	> 50,000h - L90 - B10 (Ta 25C)
W system:	36.2	Lamp code:	LED
Im source:	5300	Number of lamps for optical assembly:	1
W source:	32	ZVEI Code:	LED
Luminous efficiency (Im/W, real value):	92.22	Number of optical assemblies:	1
Im in emergency mode:	-	Power factor:	See installation instructions
Total light flux at or above an angle of 90° [Lm]:	0.0	Inrush current:	18 A / 250 µs
Light Output Ratio (L.O.R.) [%]:	63	Maximum number of luminaires of this type per miniature circuit breaker:	B10A: 21 luminaires B16A: 34 luminaires C10A: 35 luminaires C16A: 57 luminaires
Beam angle [°]:	72° / 63°	Minimum dimming %:	1
CRI:	80	Overvoltage protection:	0kV Common mode & 0kV Differential mode
Colour temperature [K]:	3000	Control:	DALI-2
MacAdam Step:	2		