## Palco InOut

Design Artec iGuzzini Studio

Last information update: February 2025

Product configuration: S851

S851: Floodlight with flange - Neutral White - Integrated power supply - DALI - Very Wide Flood - Class II




Product code

S851: Floodlight with flange - Neutral White - Integrated power supply - DALI - Very Wide Flood - Class II

## Technical description

Floodlight with LED lamp fitted with a Very Wide Flood optic. Consisting of an optical assembly made of EN1706AC 46100LF aluminium alloy and a forged steel flange for installation on cylindrical-conical poles. The optical assembly is subjected to a multistep, pre-treatment process in which the main phases are degreasing, fluorozirconation (a protective surface film) and sealing (with a nano-structured silane layer). The following painting stage consists of a primer and a liquid acrylic paint, cured at 150°C, with a high level of weather and UV ray resistance. The optical assembly is fitted with a 5 mm thick tempered sodium-calcium glass cover. The product can be positioned at 345° on the vertical plane and 90° on the horizontal plane. The product is fitted with a 7m cable hidden inside the flange and can be installed on cylindrical-conical poles using the slots in the flange. A monochrome LED circuit is located inside the product with an Opti Beam Reflector optic system. The power supply unit and DALI protocol are included in the product code. Option of using all the optic accessories that can be mounted directly on the product or via an accessory holder frame. All external screws are made of A2 stainless steel.



## Installation

Pole installations can be made using two M10 screws included in the end product code.

Colour	Weight (Kg)
White (01)   Black (04)   Grey (15)   Rust Brown (F5)	6.28

# Mounting

pole-top side entry

## Notes

S840, S841, S842, S843, S844, S845, S846, S847: Opti Beam Lens S848, S849, S850, S851: Opti Beam Reflectors Insulation class II These products can be used at a maximum ambient temperature of 50°C.

Complies with EN60598-1 and pertinent regulations















Technical data		_	
Im system:	3409	Life Time LED 1:	100,000h - L90 - B10 (Ta 25°C)
W system:	31.3	Life Time LED 2:	100,000h - L90 - B10 (Ta 40°C)
Im source:	4010	Lamp code:	LED
W source:	27	Number of lamps for optical	1
Luminous efficiency (Im/W,	108.9	assembly:	
real value):		ZVEI Code:	LED
Im in emergency mode:	-	Number of optical	1
Total light flux at or above	0	assemblies:	
an angle of 90° [Lm]:		Intervallo temperatura	from -30°C to 50°C.
Light Output Ratio (L.O.R.)			
[%]:		Power factor:	See installation instructions
Beam angle [°]:	80°	Inrush current:	21 A / 300 μs
CRI (minimum):	80	Maximum number of	
Colour temperature [K]:	4000	luminaires of this type per	B10A: 13 luminaires
MacAdam Step:	2	miniature circuit breaker:	B16A: 21 luminaires
			C10A: 21 luminaires C16A: 35 luminaires
		Overvoltage protection:	10kV Common mode & 6kV
		Overvoltage protection:	Differential mode
		Control:	DALI-2



