


Design iGuzzini iGuzzini

Product configuration: MQ55

MQ55: Recessed frame - LED - Neutral white - integrated Electronic control gear - Diffused lighting



148



141x37

MQ55: Recessed frame - LED - Neutral white - integrated Electronic control gear - Diffused lighting **Attention! Code no longer in production**

Miniaturized recessed rectangular luminaire with LEDs. Main body with die-cast aluminium radiant surface, version with perimeter surface frame. Optical system designed for diffused lighting distribution. Flux enhancer - superpure aluminium reflector - microprism screen in transparent PMMA with optimised geometry texture; a special film in acrylic material, combined with the screen, allow for a comfortable level of lighting diffusion. Black polycarbonate internal perimeter frame. Supplied with electronic control gear connected to the luminaire. High colour rendering LED.

recessed with steel springs for false ceilings from 1 to 25 mm; can be installed on ceilings and walls (vertical + horizontal) - preparation slot 37 x 141

Black / Black (43) | Black / White (47) | Grey / Black (74)

0.35

meaning
wall recessed|ceiling recessed

on power box: screw connections

Complies with EN60598-1 and pertinent regulations



IP20

IP43

On the visible part of
the product once installed




Im system:	570	CRI (typical):	97
W system:	12	Colour temperature [K]:	4000
Im source:	1000	MacAdam Step:	3
W source:	10	Life Time LED 1:	50,000h - L90 - B10 (Ta 25°C)
Luminous efficiency (lm/W, real value):	47.5	Lamp code:	LED
Im in emergency mode:	-	Number of lamps for optical assembly:	1
Total light flux at or above an angle of 90° [Lm]:	0	ZVEI Code:	LED
Light Output Ratio (L.O.R.) [%]:	57	Number of optical assemblies:	1
CRI (minimum):	95		

--

Utilisation factors

R	77	75	73	71	55	53	33	00	DRR
K0.8	45	41	38	35	40	37	37	34	60
1.0	48	44	41	39	43	41	41	38	66
1.5	53	50	47	45	49	47	46	44	76
2.0	55	53	51	49	52	50	50	47	83
2.5	57	55	53	52	54	52	52	50	87
3.0	58	56	55	54	55	54	53	51	90
4.0	59	58	57	56	57	56	55	53	93
5.0	59	58	58	57	57	57	56	54	94

Luminance curve limit



UGR diagram

Corrected UGR values (at 1000 lm bare lamp luminous flux)											
Reflect.: ceil/cav walls work pl. Room dim x y		0.70	0.70	0.50	0.50	0.30	0.70	0.70	0.50	0.50	0.30
		0.50	0.30	0.50	0.30	0.30	0.50	0.30	0.50	0.30	0.30
		0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20
		viewed crosswise					viewed endwise				
2H	2H	22.1	22.9	22.4	23.2	23.4	25.6	26.5	25.9	26.7	27.0
	3H	22.1	22.9	22.5	23.2	23.5	25.7	26.4	26.0	26.7	27.0
	4H	22.1	22.8	22.4	23.1	23.4	25.6	26.3	26.0	26.6	27.0
	6H	22.0	22.6	22.4	23.0	23.3	25.6	26.2	25.9	26.5	26.9
	8H	22.0	22.6	22.3	22.9	23.3	25.5	26.2	25.9	26.5	26.8
	12H	21.9	22.5	22.3	22.9	23.2	25.5	26.1	25.9	26.4	26.8
4H	2H	22.5	23.2	22.9	23.5	23.8	26.5	27.2	26.8	27.5	27.8
	3H	22.6	23.2	23.0	23.5	23.9	26.6	27.2	27.0	27.6	27.9
	4H	22.5	23.0	22.9	23.4	23.8	26.6	27.2	27.0	27.5	27.9
	6H	22.4	22.9	22.9	23.3	23.7	26.6	27.0	27.0	27.4	27.9
	8H	22.4	22.8	22.8	23.2	23.7	26.5	27.0	27.0	27.4	27.8
	12H	22.3	22.7	22.8	23.2	23.6	26.5	26.9	26.9	27.3	27.8
8H	4H	22.5	22.9	23.0	23.4	23.8	26.8	27.2	27.2	27.6	28.0
	6H	22.4	22.8	22.9	23.2	23.7	26.7	27.1	27.2	27.5	28.0
	8H	22.4	22.7	22.9	23.1	23.6	26.7	27.0	27.2	27.4	27.9
	12H	22.3	22.6	22.8	23.1	23.6	26.6	26.9	27.1	27.4	27.9
12H	4H	22.5	22.9	22.9	23.3	23.7	26.7	27.1	27.2	27.5	28.0
	6H	22.4	22.7	22.9	23.2	23.7	26.7	27.0	27.2	27.5	28.0
	8H	22.3	22.6	22.8	23.1	23.6	26.6	26.9	27.2	27.4	27.9
Variations with the observer position at spacing:											
S =	1.0H	1.4 / -2.0					0.4 / -0.7				
	1.5H	2.2 / -4.2					1.5 / -1.6				
	2.0H	3.5 / -6.6					2.8 / -2.3				