


N355: spotlight - warm white wide flood optic



Complies with EN60598-1 and pertinent regulations




lm system:	2278	CRI:	80
W system:	24.6	Colour temperature [K]:	3000
lm source:	3000	MacAdam Step:	2
W source:	21	Life Time LED 1:	> 50,000h - L80 - B10 (Ta 25°C)
Luminous efficiency (lm/W, real value):	92.6	Lamp code:	LED
lm in emergency mode:	-	Number of lamps for optical assembly:	1
Total light flux at or above an angle of 90° [Lm]:	0	ZVEI Code:	LED
Light Output Ratio (L.O.R.) [%]:	76	Number of optical assemblies:	1
Beam angle [°]:	54°		

	Imax=2984 cd CIE nL 0.76 97-100-100-100-76 UGR 20.2-20.2 DIN A.61 UTE 0.76A+0.00T F*1=974 F*1+F*2=999 F*1+F*2+F*3=1000 CIBSE LG3 L<1500 cd/m² at 65°	Lux			
		h	d	Em	Emax
		2	2	582	738
		4	4.1	146	184
		6	6.1	65	82
α=54°	8	8.2	36	46	

Utilisation factors

R	77	75	73	71	55	53	33	00	DRR
K0.8	68	64	61	59	63	61	61	58	77
1.0	71	68	65	63	67	65	64	62	81
1.5	75	72	70	69	71	70	69	66	88
2.0	77	75	74	73	74	73	72	70	92
2.5	79	77	76	75	76	75	74	72	95
3.0	80	79	78	77	77	77	76	74	97
4.0	80	80	79	79	78	78	77	75	99
5.0	81	80	80	80	79	79	78	76	100

Luminance curve limit



UGR diagram

Corrected UGR values (at 3000 lm bare lamp luminous flux)											
Reflect.: ceiling walls work pl. Room dim x y		viewed crosswise					viewed endwise				
2H	2H	20.8	21.5	21.1	21.7	21.9	20.8	21.5	21.1	21.7	21.9
	3H	20.7	21.3	21.0	21.5	21.8	20.7	21.3	21.0	21.5	21.8
	4H	20.6	21.1	21.0	21.4	21.7	20.6	21.1	21.0	21.4	21.7
	6H	20.5	21.0	20.9	21.3	21.7	20.5	21.0	20.9	21.3	21.7
	8H	20.5	21.0	20.9	21.3	21.6	20.5	21.0	20.9	21.3	21.6
	12H	20.5	20.9	20.8	21.2	21.6	20.5	20.9	20.8	21.2	21.6
4H	2H	20.6	21.1	21.0	21.4	21.7	20.6	21.1	21.0	21.4	21.7
	3H	20.5	20.9	20.8	21.2	21.6	20.5	20.9	20.8	21.2	21.6
	4H	20.4	20.8	20.8	21.1	21.5	20.4	20.8	20.8	21.1	21.5
	6H	20.3	20.6	20.7	21.0	21.4	20.3	20.6	20.7	21.0	21.4
	8H	20.2	20.6	20.7	21.0	21.4	20.2	20.6	20.7	21.0	21.4
	12H	20.2	20.5	20.7	20.9	21.4	20.2	20.5	20.7	20.9	21.4
8H	4H	20.2	20.6	20.7	21.0	21.4	20.2	20.6	20.7	21.0	21.4
	6H	20.2	20.4	20.6	20.9	21.3	20.2	20.4	20.6	20.9	21.3
	8H	20.1	20.3	20.6	20.8	21.3	20.1	20.3	20.6	20.8	21.3
	12H	20.0	20.2	20.5	20.7	21.2	20.0	20.2	20.5	20.7	21.2
12H	4H	20.2	20.5	20.7	20.9	21.4	20.2	20.5	20.7	20.9	21.4
	6H	20.1	20.3	20.6	20.8	21.3	20.1	20.3	20.6	20.8	21.3
	8H	20.0	20.2	20.5	20.7	21.2	20.0	20.2	20.5	20.7	21.2
Variations with the observer position at spacing:											
S =	1.0H	5.3 / -17.5					5.3 / -17.5				
	1.5H	8.1 / -21.6					8.1 / -21.6				
	2.0H	10.1 / -25.1					10.1 / -25.1				