



Last information update: May 2024

**Product configuration: 4871+1636**

4871: Projector with 50 W QR 111 dimmable electronic transformer

**Product code**4871: Projector with 50 W QR 111 dimmable electronic transformer **Attention! Code no longer in production****Technical description**

Die-cast aluminium and thermoplastic projector with adapter. It can be rotated by 340° with respect to the vertical axis and inclined by +/- 100° with respect to the horizontal axis. Rotation and inclination movements may be locked mechanically to guarantee precise positioning of the light beam - also during maintenance operations. IP40 for optical assembly with optional glass diffusers.

**Installation**

Track mounted or ceiling/wall mounted by means of the base to be ordered separately.

**Colour**

White (01) | Grey / Black (74)

**Mounting**

three circuit track

**Wiring**

Complete with dimmable electronic transformer for 50W 12V halogen lamps, inside the luminaire.

**Notes**

The luminaire becomes IP40 with the use of accessory glasses. For the photometric data of the luminaire, refer to the photometric characteristics of the light source.

Complies with EN60598-1 and pertinent regulations

**Technical data**

lm system:	443	CRI (minimum):	100
W system:	55	Colour temperature [K]:	3000
lm source:	443	Lamp maximum intensity [cd]:	2400
W source:	50	Voltage [Vin]:	12
Luminous efficiency (lm/W, real value):	8.1	Lamp code:	1636
lm in emergency mode:	-	Socket:	G53
Total light flux at or above an angle of 90° [Lm]:	0	Number of lamps for optical assembly:	1
Light Output Ratio (L.O.R.) [%]:	100	ZVEI Code:	QR 111
Beam angle [°]:	18°	Number of optical assemblies:	1

**Polar**