

**Constant current power supply unit DALI with outgoing cables IP68 60W - VIN =110-240VAC 50/60Hz
Iout = 1050mA dim. 180x90x68**

Design iGuzzini

iGuzzini

Last information update: February 2023



Accessory code

X433: Constant current power supply unit DALI with outgoing cables IP68 60W - VIN =110-240VAC 50/60Hz Iout = 1050mA dim. 180x90x68

Technical description

60W (1÷60W), 1050mA, DALI, IP68 electronic ballast with a high-strength thermoplastic box and outlet cables. Vin=100÷264Vac, 50÷60Hz Vout=57dc (SELV), Iout=1050mA

Installation

Remote installation.

Colour
Indeterminate (00)

Weight (Kg)
0.77

Dimension (mm) (*)
180x90x68

* The dimensions may change according to production requirements to ensure that performance levels and installation methods are observed.

Notes

Overvoltage protection: 5kV Common mode, 4kV differenzial mode

Complies with EN60598-1 and pertinent regulations



Technical data

Frequency [Hz]:	50/60
Current out [mA]:	1050
Inrush current:	10 A / 200 µs

Maximum number of LED power supply units of this type per miniature circuit breaker:	B10A: 18 power supply units
	B16A: 30 power supply units
	C10A: 31 power supply units C16A: 51 power supply units

Minimum dimming %: 1

Overvoltage protection:	4kV Common mode & 4kV Differential mode
-------------------------	---